




PART NUMBER	DESCRIPTION
B-0750CC1700-0170XC	COVER
B-0750SB1700-0170XF	FRAME



RoHS Compliant
 THIRD ANGLE PROJECTION 
 DO NOT SCALE DRAWING
PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ORBEL CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ORBEL CORPORATION IS PROHIBITED.

DIMENSIONS ARE IN INCHES [MILLIMETERS]
 TOLERANCES:
 FRACTIONAL: ±
 ANGULAR: MACH ± 3 Degrees
 TWO PLACE DECIMAL: ± .015 (.381)
 THREE PLACE DECIMAL: ± .010 (.254)
 MATERIAL: .010" [.254] MU-METAL, 1/2 HARD
 FINISH:
 WEIGHT: 0.096oz. (.2731g)

DRAWN	NAME	DATE
CHECKED		
ENG APPR.		
MFG APPR.		
Q.A.		

COMMENTS:


ORBEL
 ENGINEERED SOLUTIONS

SIZE **A** DWG NO. B-0750CC1700-0170XC REV. 01
 MADE FROM MU-METAL
 SCALE: 1:1 CAGE CODE: 57DU2 SHEET 1 OF 1

HOW TO ORDER BOARD LEVEL SHIELDING


The chart below is an easy-to-use reference on how Orbel BLS part numbers are created and used to order standard and custom board level shielding. Custom configurations that fall outside of our standard shield styles are also available.

Sample Part Number (Snap-Shield Bullseye™): B-0750TB1125-0250XF - TPS




STANDARD FEATURES


PIN OPTIONS




Alignment Pin




Through-Hole Pin



Through-Hole Pin with Standoff




Castellation Edge




Straight Edge, No Pin


CORNER OPTIONS



Tight Corner




Louvered Corner



Welded Corner

ADDITIONAL OPTIONS



Trace Notch



Pick Target



Ventilation Holes



Logo or Part Number Marking

PERFORMANCE Specs

Material Options

- Nickel Silver
- TPS: Tin-Plated Steel
- TPB: Tin-Plated Brass
- TPC: Tin-Plated Copper

Co-Planarity

- Smaller Shields: 0.004"
- Larger Shields: 0.008"

Material Thicknesses

- 0.010" (Standard)
- 0.008"
- 0.012"
- 0.015"

RoHS-Compliant

- Yes

Shielding Effectiveness

- Up to 60dB

Other material options include beryllium copper, phosphorus bronze, and stainless steel. Additional plating finishes available upon request.

All technical data presented herein is accurate to the best of our knowledge based on Orbel's most up-to-date testing information and material specs. This information is not presented as a warranty or guarantee and is not intended to be all-inclusive as to conditions of use.