

## Han 16B Ex-HBM-Double Lever



Image is for illustration purposes only. Please refer to product description.

Part number	09 36 016 1301
Specification	Han 16B Ex-HBM-Double Lever
HARTING eCatalogue	<a href="https://b2b.harting.com/09360161301">https://b2b.harting.com/09360161301</a>

### Identification

Category	Hoods/Housings
Series of hoods/housings	Han® Ex
Type of hood/housing	Bulkhead mounted housing

### Version

Size	16 B
Locking type	Double locking lever
Field of application	Connectors for explosion hazardous environments
Details	ATTENTION! Only to be used with Han® Ex inserts!

### Technical characteristics

Limiting temperature	-20 ... +40 °C
Degree of protection acc. to IEC 60529	IP65 With cable gland

### Material properties

Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 5015 (sky blue)
Material (seal)	NBR
Material (locking)	Stainless steel
RoHS	compliant
ELV status	compliant
China RoHS	e

## Material properties

REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel Lead Naphthalene

## Commercial data

Packaging size	1
Net weight	274 g
Country of origin	China
European customs tariff number	85389099
eCl@ss	27440202 Shell for industrial connectors