

## Specification Sheet

Part Number: 170-03071



Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.

Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.

Braided Sleeving, Expandable, Flame Retardant, 0.125" Dia, PET, Gray, 225 ft/reel

**Article Number** 170-03071

**Type** BSPFR188

**Color** Gray (GY)

**Quantity Per** reel

**Product Description** A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.

**Short Description** Braided Sleeving, Expandable, Flame Retardant, 0.125" Dia, PET, Gray, 225 ft/reel

**Global Part Name** BSPFR188-PET-GY

**Length L (Imperial)** 225.0

**Length L (Metric)** 68.6

**Bundle Diameter Min (Imperial)** 0.094

**Bundle Diameter Min (Metric)** 2.4

**Bundle Diameter Max (Imperial)** 0.25

**Bundle Diameter Max (Metric)** 6.4

**Diameter D (Imperial)** 0.13

**Diameter D (Metric)** 3.2

**Nominal Diameter (Imperial)** 0.125

**Nominal Diameter (Metric)** 3.18

**Material** Polyester (PET)

**Material Shortcut** PET

**Flammability** FAR 25 Mil-202 FMVSS 302 UL VW-1

**Halogen Free** Yes

**Operating Temperature** -94°F to +257°F (-70°C to +125°C)

**Reach Compliant (Article 33)** Yes

**ROHS Compliant** Yes

**Certification/Specification** UL 94 VW-1

**UL Recognized (US)** Yes

**Package Quantity (Imperial)** 225

**Package Quantity (Metric)** 68.58

**Customs Number** 5808100000