

ALISE-70-M

~24° medium beam

TECHNICAL SPECIFICATIONS:

Dimensions	Ø 70.0 mm
Height	42 mm
ROHS compliant	yes ⓘ




MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish	Coating
ALISE-70-M	Reflector	Aluminium	metal		Anodized

ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
C16904_ALISE-70-M	500	100	25	8.7
» Box size: 410 x 335 x 200 mm				




See also our general installation guide: www.ledil.com/installation_guide

PHOTOMETRIC DATA (SIMULATED):





LED	V13 Gen7
FWHM / FWTM	22.0° / 46.0°
Efficiency	92 %
Peak intensity	4.4 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



CITIZEN


LED	CLL03x/CLU03x
FWHM / FWTM	22.0° / 48.0°
Efficiency	91 %
Peak intensity	4.2 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



CITIZEN



LED	CLL03x/CLU03x
FWHM / FWTM	28.0° / 60.0°
Efficiency	74 %
Peak intensity	2.4 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	

C17098_ALISE-70-DL



LUMILEDS

LED	LUXEON CoB 1204/1205
FWHM / FWTM	22.0° / 44.0°
Efficiency	92 %
Peak intensity	4.5 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	




PHOTOMETRIC DATA (SIMULATED):

LUMILEDS

LED	LUXEON CoB 1204/1205
FWHM / FWTM	24.0° / 50.0°
Efficiency	83 %
Peak intensity	3.4 cd/lm
LEDs/each optic	1
Light colour	White

Required components:




LUMILEDS

LED	LUXEON CoB 1208
FWHM / FWTM	28.0° / 60.0°
Efficiency	74 %
Peak intensity	2.3 cd/lm
LEDs/each optic	1
Light colour	White

Required components:


C17098_ALISE-70-DL



LUMILEDS

LED	LUXEON CoB 1208
FWHM / FWTM	24.0° / 50.0°
Efficiency	92 %
Peak intensity	4 cd/lm
LEDs/each optic	1
Light colour	White


Required components:




SAMSUNG

LED	LC016D / LC019D / LC026D / LC033D
FWHM / FWTM	26.0° / 54.0°
Efficiency	91 %
Peak intensity	3.7 cd/lm
LEDs/each optic	1
Light colour	White

Required components:



PHOTOMETRIC DATA (SIMULATED):



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

**Ledil Optics Technology
(Shenzhen) Co., Ltd.**
405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

**Local sales and technical
support**
www.ledil.com/
where_to_buy

Shipping locations
Salo, Finland
Hong Kong, China

Distribution Partners
www.ledil.com/
where_to_buy