

## **Specification Sheet**

Part Number: 596-00234

Pre-Printed Vinyl Solar Labels are made with UV-stable inks and materials for durability and weather resistance.

Supplied with an aggressive adhesive to ensure long life.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

ELECTRICAL SHOCK HAZARD
IF A GROUND FAULT IS INDICATED,
NORMALLY GROUNDED CONDUCTORS
MAY BE UNGROUNDED AND ENERGIZED

Pre-printed labels offer significant time and cost savings over high priced plastic engraved phenolic placards and lead time purchased markers.

Solar Label, WARNING GROUNDED CONDUCTORS ENERGIZED..., 4.125" x 2.0", VL, Red, 50/roll

Article Number 596-00234

**Type** WGCME

Color Red (RD)

Quantity Per roll

**Product Description** 

HellermannTyton pre-printed Solar Installation Labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description	Solar Label, WARNING GROUNDED CONDUCTORS ENERGIZED, 4.125" x 2.0", VL, Red, 50/roll
Global Part Name	WGCME-443/281-RD
Technical Description	Pre-Printed Solar Label, "WARNING - GROUNDED CONDUCTORS ENERGIZED", 4.12" X 2", Red
Width W (Imperial)	4.125
Width W (Metric)	104.6
Thickness T (Imperial)	0.0025
Thickness T (Metric)	64.0
Height H (Imperial)	2.0
Height H (Metric)	50.8
Material	Type 443/281, UV-stabilized flexible white vinyl with clear polyester laminate (443/281)
Material Shortcut	443/281
Adhesive	Acrylic

No

Halogen Free

Adhesive Operating Temperature -40°F to +174°F (-40°C to +79°C)

**Operating Temperature**  $-40^{\circ}\text{F to } +174^{\circ}\text{F } (-40^{\circ}\text{C to } +79^{\circ}\text{C})$ 

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Certification/Specification UL 969 NEC2011

Warranty (US) Yes

UL Recognized (US) Yes

Package Quantity (Imperial) 50

Package Quantity (Metric) 50

Customs Number 3919102055

Labels per Column 1

Labels per Row 1