



Thread and locking adapter, Material: Polyamide PA 6.6, glass-fibre reinforced, Colour: Black

RAL: 9005

Business data

Article number	28777.4
Article name	KDS-RGA M63 BK
GTIN (EAN)	4044211234577
Colour	Black
Packaging unit	5
Quantity unit	PC
Weight per piece (not including packaging)	20.15 g
Weight per piece (including packaging)	20.2 g
Unit of weight	G
Customs number	39259020
Country of origin	DE
Product description	Cable Entry

Technical data

Dimensions

Length	70 mm
Length of wall cutout	63.4 mm
Width	70 mm
Width of wall cutout	63.4 mm
Height	22.1 mm
Installation height	14.9 mm

Thread

Thread type	Metric
Thread size	63 mm
Thread pitch	1.5 mm
Thread length (L)	14.9 mm

Materials

Material	Polyamide 6.6
Glass-fibre reinforced	✓
Flammability class UL 94	V-0
Working temperature, min.	-40 °C
Working temperature, max.	120 °C
Halogen-free	✓
Silicone-free	✓

Further technical data

Mounting type	Screws
Degree of protection	IP66
NEMA Type	1, 12, 4x (indoor use only)
Torque for the locknut	7 Nm

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2022-01-07
REACH Candidate Substance Note	No
RoHS Conform	yes

Approvals

UL Recognized

UL File Number	E489821
UL approval	UL 508A
UL Recognized	yes

cUL Recognized

cUL approval	C22.2 No. 14-18
cUL File Number	E489821
cUL Recognized	yes

Media



Accessories

Small Seals

Big Seals

##INVERSE##CONTA-CABLE



Round cable entry, Material: polyamide PA 6.6, glass-fibre reinforced | TPE, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
28774.4	KDS-R 40-63 BK	4044211234546	5 ST

Separable locknut

Sheet-metal puncher