


PROPRIETARY INFORMATION:

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC.

REVISION

REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE, RFS. 27373	06/18/19	MK



GENERAL SPECIFICATIONS:

RATING: 13A / 125V AC
 CABLE TYPE / SIZE: SPT-3, # 3 x 16 AWG
 TEMPERATURE RATING: 60° C
 CONDUCTOR COLORS: BLACK SMOOTH/ BLACK RIBBED / GREEN

OVERALL LENGTH: 2030 ± 50 mm
 CABLE OUTER DIAMETER: 5x11 mm Nominal
 END 'A' PLUG: NEMA 5-15P
 END 'B': SEE TERMINATION TABLE
 APPROVALS PLUG: UL, CSA OR cUL
 APPROVALS CABLE: UL, CSA OR cUL

PACKING:

HANKING


NOTES:

1. CORD AND PLUG MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).

Customer Approval of Specification:

Please approve, sign and send back to GlobTek so we can complete order processing. A delay in receipt of this form will delay delivery schedule.

Company Name:
 Customer P/N:
 Quote Number:
 Date:
 Auth. Rep. Name:
 Auth. Rep. Signature:

CONDUCTOR TERMINATION TABLE:

Wire	Color	Split ±5 mm	RIJ ± 1 mm	Terminal
Wire 1	Black Smooth	127	-	Quick Disconnect (note 1)
Wire 2	Green	127	10	Partial Strip
Wire 3	Black Ribbed	127	10	Partial Strip



OR



RELEASED
 By PUCXD
 2:23 pm, Jun 20, 2019


NOTE:

1. Black conductor has fully insulated Molex disconnect P/N: BB5263 or equivalents

Foot Note:
 Globtek Inc. will not be liable for the safety and performance of these power product if unauthorized access and repair occurs. End user should consult the applicable UL, CSA or EN Standards for proper installation instruction.

Limitation of Use:
 Globtek product are not authorized for use as mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.

Contents of this document are subject to change without prior notice

DASH NO.	PART NO	REV.	DESCRIPTION	NOTES
TABULATION BLOCK				
INIT.BY: NF		DATE: 06/18/19	GlobTek, Inc. 186 Veterans Dr. Northvale, NJ 07647 Tel. 201-784-1000 Fax 201.784.0111 www.globtek.com	
DRAWN: NF		DATE: 06/18/19		
APRVD: BS		DATE: 06/18/19	SCALE: NONE	PART NO: 3021616F7000(R)
DWG TITLE: NORTH AMERICAN NON-DETACHABLE CORDSET				REV. A
				SHEET 1/1

TOLERANCES:
 DECIMALS ANGULAR
 .xx +/- 0.1 +/- 1°
 .xxx +/- .005
 MILLIMETERS ANGULAR
 .xx +/- 0.3 +/- 1°
 .xxx +/- .013

FSCN No.:
 G, CC, YL
 SIZE
 A