





ASSEMBLED VIEW




- NOTES:
- 1) CORD GRIP RANGE: 16mm TO 17mm
 - 2) CONTACT BARREL RANGE: 16AWG TO 18AWG
 - 3) RECOMMENDED CRIMP TOOLS:
 - HAND CRIMPER: MFX-3959
 - PNEUMATIC CRIMPER: MFX-3960
 - 4) EXTRACTION TOOL: QXRT16
 - 5) MATERIALS:
 - HOUSING BODY: ZINC DIE CAST, NICKEL PLATED
 - COUPLING NUT: ALUMINUM ALLOY, NICKEL PLATED
 - WAVE SPRING: STAINLESS STEEL
 - INSULATION INSERT: PA66, UL94/V-0
 - CONTACT: BRASS, GOLD FLASH PLATED
 - SEAL AND O-RING: SILICONE
 - 6) ELECTRICAL DATA:
 - a) CURRENT (MAX): 3A
 - b) VOLTAGE (MAX): 500VAC
 - c) INSULATION RESISTANCE (MIN): 5000M OHMS
 - d) TEST VOLTAGE (BETWEEN CONTACTS): 3050V

- 7) TECHNICAL DATA:
- a) TEMPERATURE RANGE: -40°C TO 115°C
 - b) PROTECTION: IP67 (IP69K WHEN IN MATED CONDITION)
 - c) MATING CYCLES: >500
 - d) VIBRATION RESISTANCE PER MIL-STD-202 METHOD 204
 - e) THERMAL SHOCK PER MIL-STD-202 METHOD 207
 - f) 48 HOUR SALT SPRAY PER MIL-STD-202 METHOD 101

8) RoHS COMPLIANT

REVISIONS					
REV	ECO	DESCRIPTION	DATE	BY	APPR
01	-	RELEASE NEW DWG FORMAT	-	-	-
02	-	ADDED IP69K RATING	4/21/2020	RO	DR

ILLUSTRATION: COMPLETE KIT



28	MP16M23F	CONTACT, PIN, SIZE 16	3
1	RT0L-20CPG-S1	CORD GRIP	2
1	RT062028PNH03SS	CONNECTOR	1
QUANTITY	PART NUMBER	DESCRIPTION	ITEM
MATERIALS LIST			
UNLESS OTHERWISE SPECIFIED		SIGNATURES	DATE
1) All dimensions are in metric(mm).		DRAWN: MRF	21AUG18
2) Tolerances are as follows:		CHECKED:	
1 PL DEC ±0.30		ENGINEER:	
2 PL DEC ±0.15		APPROVAL:	
3 PL DEC ±0.08		CUSTOMER:	
3) Note reference =		THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS.	
MATERIAL SPECIFICATIONS:		KIT, ECO-MATE RM	
PROCESS SPECIFICATIONS:		SIZE B C- RT062028PNH03SS-K	
NEXT ASSY:		REVISION 02	
		SCALE: NONE	SHEET 1 OF 1

TITLE:	KIT, ECO-MATE RM	DWG NO:	REV: 01	SH: 1	DF: 1
--------	------------------	---------	---------	-------	-------