

A.
Featured
Products

B.
Copper
Systems

C.
Fiber
Systems

D.
Faceplates,
Frames &
Surface
Mount Boxes

E.
Industrial
Networks

F.
Audio
Video
Systems

G.
Keystone
Cabling
Systems

H.
Zone
Cabling

J.
Cable
Routing
Systems

K.
Surface
Raceway

L.
Cabinets
& Rack
Systems

M.
Power
Management

N.
Grounding
& Bonding

O.
Identification
Products

P.
Cable
Management
Accessories

Q.
Part
Number
Index

€ Elastomeric Cable Ties

- Elastic material provides a flexible tie body that safely contours around cable bundle, preventing over-tensioning of data cables to maintain network integrity
- UL 94V-0 material provides greater flame resistance; meets stringent telecommunication flammability requirements (such as NEBS GR-63-CORE)
- Soft material has no sharp edges; protects the installer and the cable bundle
- High coefficient of friction grips and prevents lateral movement along cable bundle
- Releasable and re-usable to accommodate frequent moves, adds, and changes
- Halogen-free, non-toxic, and environmentally safe material will not release toxic or corrosive gases upon combustion
- Locking head design; the tapered tip threads into locking head to speed productivity; industry-accepted intuitive tie design



Part Number	Length		Width		Thickness		Max. Bundle Dia.		Min. Loop Tensile Str.		Recommended Installation Tool	Std. Pkg. Qty.	Std. Ctn. Qty.
	In.	mm	In.	mm	In.	mm	In.	mm	Lbs.	N			
ERT2M-C20	8.50	216.0	0.50	12.7	0.09	2.3	2.35	59.7	18	80	Hand install only	100	1000
ERT3M-C20	11.00	279.0					3.00	76.2					
ERT4.5M-C20	16.00	406.0					4.50	114					

Part Number System for Elastomeric Cable Ties

ERT

Type

ERT = Elastomeric Releasable Tie

2

Size

Approx. Maximum Bundle Dia. (In.)

M

Cross Section

M = Miniature

—

C

Package Size

C = 100

—

Material/Color

See chart below

Material and Color Chart

Material	Color	Panduit Suffix
TPU	Black	20