


Connector Location A


Connector Location B



Mating face acc. to IEC 61076-2-104

M8 4-pole, straight overmolded, unshielded


X
female



Loading-Plan

- 1 brown
- 2 white
- 3 blue
- 4 black

- Protection level: IP67
- Temperature range: -25°C ... +80°C



4.0 to 4.0	±1%
0.1 to 3.9	+0.04
a [m]	Tolerance

length in "1m" step	40	XXX=400
	39	XXX=390
	.	.
	12	XXX=120
	11	XXX=110
length in "0.1m" step	10	XXX=100
	9.9	XXX=099
	9.8	XXX=098
	.	.
	0.4	XXX=004
	0.3	XXX=003
	0.2	XXX=002
	0.1	XXX=001
Step	a [m]	XXX

PUR black, 4x0.25mm ²	21348100489XXX
Type of cable	Part no.

All Dimensions in mm		Tech. Character.		Free size tol.		According to production drawing	
All rights reserved		Created by STOCHECIC Stocheci		Inspected by COSTEA Costea		Standardisation MUNTEANV Muntean	
Department HCS - RO		Date 2019-01-11		State Final Release		Doc-Key / ECM-Nr. 100809670/UGD/009/A 500000145294	
HARTING Customised Solutions		Title M8 Cable Assembly 4-poles st/- f/-		Rev. A		Page 1/1	
D-32339 Espelkamp		Type TB		Number 21348100489XXX			