

2N2221A
2N2222A

SILICON
NPN TRANSISTORS



www.centralsemi.com



TO-18 CASE

MAXIMUM RATINGS: (T_A=25°C)

	SYMBOL	UNITS
Collector-Base Voltage	V _{CBO}	V
Collector-Emitter Voltage	V _{CEO}	V
Emitter-Base Voltage	V _{EBO}	V
Continuous Collector Current	I _C	mA
Power Dissipation	P _D	mW
Power Dissipation (T _C =25°C)	P _D	W
Operating and Storage Junction Temperature	T _J , T _{stg}	°C
Thermal Resistance	Θ _{JA}	°C/W
Thermal Resistance	Θ _{JC}	°C/W

ELECTRICAL CHARACTERISTICS: (T_A=25°C unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	MAX	UNITS
I _{CBO}	V _{CB} =60V	10		nA
I _{CBO}	V _{CB} =60V, T _A =150°C	10		µA
I _{CEV}	V _{CE} =60V, V _{EB} =3.0V	10		nA
I _{EBO}	V _{EB} =3.0V	10		nA
BV _{CBO}	I _C =10µA	75		V
BV _{CEO}	I _C =10mA	40		V
BV _{EBO}	I _E =10µA	6.0		V
V _{CE(SAT)}	I _C =150mA, I _B =15mA		0.3	V
V _{CE(SAT)}	I _C =500mA, I _B =50mA		1.0	V
V _{BE(SAT)}	I _C =150mA, I _B =15mA	0.6	1.2	V
V _{BE(SAT)}	I _C =500mA, I _B =50mA		2.0	V

		2N2221A		2N2222A	
		MIN	MAX	MIN	MAX
h _{FE}	V _{CE} =10V, I _C =0.1mA	20	-	35	-
h _{FE}	V _{CE} =10V, I _C =1.0mA	25	-	50	-
h _{FE}	V _{CE} =10V, I _C =10mA	35	-	75	-
h _{FE}	V _{CE} =10V, I _C =10mA, T _A =-55°C	15	-	35	-
h _{FE}	V _{CE} =10V, I _C =150mA	40	120	100	300
h _{FE}	V _{CE} =1.0V, I _C =150mA	20	-	50	-
h _{FE}	V _{CE} =10V, I _C =500mA	25	-	40	-

R5 (5-December 2013)


2N2221A
2N2222A

SILICON
NPN TRANSISTORS

Central
Semiconductor Corp.™

SYMBOL	TEST CONDITIONS	2N2221A		2N2222A		UNITS
		MIN	MAX	MIN	MAX	
f_T	$V_{CE}=20V$, $I_C=20mA$, $f=100MHz$	250	-	300	-	MHz
C_{ob}	$V_{CB}=10V$, $I_E=0$, $f=100kHz$	-	8.0	-	8.0	pF
C_{ib}	$V_{EB}=0.5V$, $I_C=0$, $f=100kHz$	-	25	-	25	pF
h_{ie}	$V_{CE}=10V$, $I_C=1.0mA$, $f=1.0kHz$	1.0	3.5	2.0	8.0	k Ω
h_{ie}	$V_{CE}=10V$, $I_C=10mA$, $f=1.0kHz$	0.2	1.0	0.25	1.25	k Ω
h_{re}	$V_{CE}=10V$, $I_C=1.0mA$, $f=1.0kHz$	-	5.0	-	8.0	$\times 10^{-4}$
h_{re}	$V_{CE}=10V$, $I_C=10mA$, $f=1.0kHz$	-	2.5	-	4.0	$\times 10^{-4}$
h_{fe}	$V_{CE}=10V$, $I_C=1.0mA$, $f=1.0kHz$	30	150	50	300	
h_{fe}	$V_{CE}=10V$, $I_C=10mA$, $f=1.0kHz$	50	300	75	375	
h_{oe}	$V_{CE}=10V$, $I_C=1.0mA$, $f=1.0kHz$	3.0	15	5.0	35	μS
h_{oe}	$V_{CE}=10V$, $I_C=10mA$, $f=1.0kHz$	10	100	25	200	μS
$r_b'C_C$	$V_{CB}=10V$, $I_E=20mA$, $f=31.8MHz$	-	150	-	150	ps
NF	$V_{CE}=10V$, $I_C=100\mu A$, $R_S=1.0k\Omega$, $f=1.0kHz$	-	-	-	4.0	dB
t_d	$V_{CC}=30V$, $V_{BE}=0.5V$, $I_C=150mA$, $I_{B1}=15mA$	-	10	-	10	ns
t_r	$V_{CC}=30V$, $V_{BE}=0.5V$, $I_C=150mA$, $I_{B1}=15mA$	-	25	-	25	ns
t_s	$V_{CC}=30V$, $I_C=150mA$, $I_{B1}=I_{B2}=15mA$	-	225	-	225	ns
t_f	$V_{CC}=30V$, $I_C=150mA$, $I_{B1}=I_{B2}=15mA$	-	60	-	60	ns

TO-18 CASE - MECHANICAL OUTLINE



SYMBOL	DIMENSIONS			
	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A (DIA)	0.209	0.230	5.31	5.84
B (DIA)	0.178	0.195	4.52	4.95
C	-	0.030	-	0.76
D	0.170	0.210	4.32	5.33
E	0.500	-	12.70	-
F (DIA)	0.016	0.019	0.41	0.48
G (DIA)	0.100		2.54	
H	0.050		1.27	
I	0.036	0.046	0.91	1.17
J	0.028	0.048	0.71	1.22

TO-18 (REV: R1)

LEAD CODE:

- 1) Emitter
- 2) Base
- 3) Collector

MARKING: FULL PART NUMBER

R5 (5-December 2013)

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix " TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix " PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.

145 Adams Avenue

Hauppauge, NY 11788 USA

Main Tel: (631) 435-1110

Main Fax: (631) 435-1824

Support Team Fax: (631) 435-3388

www.centralsemi.com

Worldwide Field Representatives:

www.centralsemi.com/wwreps

Worldwide Distributors:

www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms

Product End of Life Notification

PDN ID:	PDN01195
Notification Date:	10/20/21
Last Buy Date:	4/20/22
Last Shipment Date	10/20/22

Summary: The CP225 wafer process is discontinued and now classified as End of Life (EOL).

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by other manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's ongoing Product Management Process. Any replacement products are noted below. The effective date for placing last purchase orders will be six (6) months from the date of this notice and twelve (12) months from the notice date for final shipments, and minimum order quantities may apply. The last purchase and shipment dates may be extended if inventory is available.

*** All Plating types (PBFREE, TIN/LEAD) for each item listed are included in this notice.**

Central Part Number	Suggested Replacement
CP225-2N2218A-WN	N/A
2N2218A	N/A
2N2221A	N/A

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. If you would like assistance, please visit <https://my. centralesemi.com/submit-inquiry?type=ER> to submit an online inquiry.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.