


**NOTES:**

1. SEE CURRENT CATALOG FOR ADDITIONAL PART SUFFIXES TO INDICATE PACKAGE QUANTITY.
2. THE FIBERRUNNER 6-4 LOW PROFILE REDUCER IS DESIGNED WITH A MINIMUM 2" (50.8) BEND RADIUS TO PROTECT FIBER OPTIC CABLES.
3. THE FIBERRUNNER 6-4 LOW PROFILE REDUCER ALLOWS FOR FIBER-DUCT 4x4 SOLID OR SLOTTED WALL CHANNEL TO BE INSERTED INTO THE VERTICAL EXIT END OF THE FIBERRUNNER 12x4 VERTICAL TEE FITTING.
4. DIMENSIONS IN PARENTHESES ARE IN METRIC.

PANDUIT PART NUMBER	WEIGHT
FRLPR64BL	0.45 LB/EACH (206g/EACH)



ENG. REF.: D38671BC_DC_FRLPR64BL_01.prt

CAD FILENAME/LAYERS



FRLPR64BL.pdf

PANDUIT CORP. TINLEY PARK, ILLINOIS

**FIBERRUNNER 6-4 LOW PROFILE
REDUCER (FRLPR64BL)**

CUSTOMER DRAWING

UNLESS OTHERWISE SPECIFIED,
DIMENSIONAL TOLERANCES ARE:

(.X) ± (.XXX) ±
(.XX) ± .03 (.8) ANGLES ±

UNLESS OTHERWISE SPECIFIED,
ALL DIMENSIONS ARE GIVEN IN
INCHES, THIRD ANGLE PROJECTION.

DRAWN BY
JHNU

DATE
10-9-03

CHK'D
RPA

MAT'L:

ABS AND STEEL

SCALE
NONEDRAWING NO.
38671-03DWG
A
SIZE

REV	DATE	BY	CHK	DESCRIPTION	ECN	R	CUST	SUP	GMBH
-	-----	---	---	F. REVISED PART WEIGHT	-----	--	--		
-	-----	---	---	E. REVISED GENERAL NOTES D. REVISED CAD FILENAME	-----	--	--		
2	7-6-06	DTP	RN	C. REVISED DRAWING TITLE B. REVISED AND REDRAWN	38671-03	RN	RN		