

General Specifications

Motor Type: DC Brushless Motor

Motor Protection: Auto Restart/Polarity Protection

Motor withstands reverse connection for positive and negative leads.

Insulation Resistance:

10M Ω or over with a DC500V Megger

Dielectric Withstand Voltage:

AC 700V 1s or 500V 1min


Allowable Ambient Temperature Range:

-10°C ~ +70°C (Operating)

-40°C ~ +70°C (Storage)

(non-condensing environment)

Characteristics Curves



PWM Benefits & Applications

PWM Benefits

- Increased Life Expectancy
- Energy Saving
- Lower Vibration
- Lower Noise
- Current Spike Prevention

PWM Applications

- Routers
- Switches
- Storage
- Data Centers
- Optical Repeaters
- Broadcast Equipment
- Inverters
- UPS
- Battery Chargers
- Fuel Cells
- Industrial Power Supplies
- Welders
- Plasma Cutters
- Instrumentation
- Test Equipment
- Enclosures and more

- Customized fan performances at multiple operating points.
- Peak efficiency resulting in lower total ownership costs.
- Cost effective and better reliability.

Life Expectancy L10

25°C 90,000 Hours


Specifications

MODEL	Rated Voltage	Operating Voltage	Current		Input Power		Speed	Max. Air Flow		Max. Static Pressure		Noise	Mass
	(V)	(V)	Avg	Max	Avg	Max	(min ⁻¹) ¹	(CFM)	(m³/min)	(inH₂O)	(Pa)	(dB) ¹	(g)
	(V)	(V)	(A) ¹	(A) ¹	(W) ¹	(W) ¹	(min ⁻¹) ¹	(CFM)	(m³/min)	(inH₂O)	(Pa)	(dB) ¹	(g)
06025SA-12T-AU-D3	12	10.8 ~ 13.2	0.43	0.66	5.16	7.92	7500	37.8	1.07	0.64	158.5	47.0	65

*1: Values in Free Air

PWM Specifications


PWM CONTROL ● CONNECTION



1. PWM Control

V_{st} = Low Level (0V~0.4V) → Low Speed(On Duty 0%)
 V_{st} = High Level (4.0V~5.0V) → Full Speed(On Duty 100%)
 V_{st} = Open → Full Speed

2. PWM Duty & PWM Input Pulse



PWM Duty means that a ration of high level time (t)/PWM Input Pulse(T).


$(t/T) \times 100$: On Duty 0% ~ 100%

PWM Frequency $f = 25[\text{kHz}]$

TACHO Specifications

TACHOMETER SIGNAL

1. OUTPUT CIRCUIT : OPEN COLLECTOR
2. SPECIFICATION
 $T_a = 25^\circ\text{C}$
 Absolute Maximum Ratings at $T_a = 25^\circ\text{C}$
 V_{ce} max : +15V
 I_c max : 5mA [$V_{ce}(\text{sat})$ max = 0.5V]




TACHO SIGNAL CIRCUIT

PWM Characteristics Curve

Duty Vs Speed Curve

<Reference Value>

At Rating Voltage, $V_{st}(H) = 5.0\text{V}$, $f = 25\text{kHz}$, $T_a = 25^\circ\text{C}$



3. The condition for PWM control are as follows.


•When you use this under PWM control, always be sure the motor's operation under practical mounting state.

•Fan motor may not start up caused by PWM control at very low speed condition.


•To run at Rating Voltage.

3. OUTPUT WAVEFORM : AT RATED VOLTAGE OUTPUT SIGNAL VOLTAGE

3-1 Case-1



3-2 Case-2




- 1) When the rotor is locked at V_OH position of signal, signal keeps V_OH position.
- 2) When the rotor is locked at V_OL position of signal, signal keeps V_OL position.
- 3) $T = T1 + T2 + T3 + T4 = 60/m = 1$ rotation

m : min - 1

Tach Duty Cycle = $50\% \pm 10\%$

Panel Cut-Outs




Materials




Casing : Plastic (Black UL94V-0)
 Impeller : Plastic (Black UL94V-0)
 Bearing : Ball Bearing
 Lead Wire : UL10368 AWG26
 (+) : Red (-) : Black
 PWM : Brown Tach : White

Outline

Name Plate



RIB TYPE



Unit: mm (inch)