

# AR884CHSC



Sample image

**Order symbol:** AR884CHSC

**Product nbr:** 8561086

**Description:** PC Enclosure

**Remarks:** Hinged opaque screw cover

**EAN:** 6418074066510

**El. number:**

- Finland:
- Denmark:
- Sweden:

**Including:** Hinged screw cover. Base with 10-32 brass inserts, cover with formed in place PUR gasket, stainless hinge pin and 2 cover screws. Enclosure mounting foot kit. Accessory 10-32 screws for panel mounting.

ARCA-8x8\_combi

| Dimensions: | Height | Width | Depth |
|-------------|--------|-------|-------|
| mm:         | 203    | 203   | 102   |
| inch:       | 8      | 8     | 4     |

## Materials:

|                  |                      |
|------------------|----------------------|
| Material:        | Polycarbonate        |
| Base colour:     | RAL 7035 -light grey |
| Cover colour:    | RAL 7035 -light grey |
| Gasket material: | Polyurethane         |

## Temperatures:

|                               |             |
|-------------------------------|-------------|
| Temperature °C (short term):: | -40 ... 140 |
| Temperature °C (continuous):  | -40 ... 80  |
| Temperature °F (short term):  | -40 ... 250 |
| Temperature °F (continuous):  | -40 ... 175 |

## Accessories:

|        |                                               |
|--------|-----------------------------------------------|
| ALBP88 | Aluminum Back Panel<br>(175 x 175)            |
| ABP88  | Painted Steel Back Panel<br>(175 x175)        |
| ASP88  | Aluminum Swing Panel<br>(204.4 x 204.5 x 0)   |
| ASPHK8 | Swing Panel Kit w/o Panel                     |
| APBP88 | PVC Back Panel<br>(175 x 175)                 |
| ADFP88 | Dead Front Panel w/ screws<br>(175 x 175 x 0) |
| ASPK88 | Swing Panel Kit incl. Panel                   |
| AMFL8  | 8" Mounting Flange Set                        |

## Rating:

|                                        |                            |
|----------------------------------------|----------------------------|
| Ingress protection (EN 60529):         | IP66; IP67;                |
| Impact Resistance (EN 62262):          | IK09;                      |
| Electrical insulation:                 | Not insulated              |
| Halogen free (DIN/VDE 0472, Part 815): | 1                          |
| UV resistance:                         | UL 508                     |
| Flammability Rating:                   | UL 508                     |
| Glow Wire Test (IEC 695-2-1) °C:       | 960 °C                     |
| NEMA Class                             | NEMA 4, 4X, 6, 6P, 12, 12K |

**Certificates:**

ARCA\_CertificateofCompliance