

Identification strips



For type I, II extractor handle and type IV injector/extractor handle
Width 4 HP

Packs of	Order No.
100	3684.328


Injector/extractor handle type IVs



With push-button

For inserting and removing connectors with a large number of pins. A metal insert ensures reliable functioning, even at forces of up to 815 N.

- Insertion/removal function
- Push-button for locking and unlocking the board type plug-in unit (cannot be extracted in the locked position)
- Optionally with ½ HP offset PCB attachment, e. g. for component mounting on both sides
- Optional integral micro-switch for "live insertion" applications
- ESD pin to dissipate static charges before contacting the connectors and for precise positioning of the board type plug-in unit
- Keyable
- Integral PCB attachment
- Bayable



Material:

Plastic/metal

Supply includes:

Assembly parts.

Note:

- Insertion only when used with front horizontal rails, with 10 mm extension (B, B1, B2), see page 109-110
- With 3 U front panels, only one extractor handle is required.

Handles without offset

Installation	Packs of	Order No.
top	1	3688.770
bottom	1	3688.771

Handles with ½ HP offset

Installation	Packs of	Order No.
top	1	3688.772
bottom	1	3688.773

+ Accessories:

Keys, see page 124
Keyable guide rails, see page 120
Keyable guide rails with 1/2 HP offset, see page 121
Micro-switches, see page 141
Connector pin for baying, see page 139

Connection pin



For injector/extractor handles, types IV, IVs and VII

The connection pin can be used to connect injector/extractor handles, types IV, IVs and VII.

Material:

Steel

Packs of	Order No.
20	3685.319