

SB12AFC ~ SB16AFC Series

Surface Mount Schottky Barrier Rectifier

Voltage 20~60 V **Current** 1 A



Features

- Low power loss, high efficiency
- High surge current capability
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

Mechanical Data

- Case : Molded plastic, SMAF-C
- Terminals : Solderable per MIL-STD-750, Method 2026
- Approx. Weight : 0.0012 ounces, 0.034 grams

SMAF-C



Maximum Ratings and Thermal Characteristics (T_A = 25°C unless otherwise noted)

PARAMETER	SYMBOL	SB12AFC	SB13AFC	SB14AFC	SB15AFC	SB16AFC	UNIT
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	20	30	40	50	60	V
Maximum RMS Voltage	V _{RMS}	14	21	28	35	42	V
Maximum DC Blocking Voltage	V _R	20	30	40	50	60	V
Maximum Average Forward Rectified Current	I _{F(AV)}	1					A
Peak Forward Surge Current : 8.3 ms Single Half Sine-Wave Superimposed On Rated Load	I _{FSM}	30					A
Instantaneous Forward Voltage at 1A	V _F	0.5			0.7		V
Reverse Current ^(Note 3)	I _R	0.2			0.1		mA
Typical Junction Capacitance Measured at 1 MHz And Applied V _R = 4V	C _J	45					pF
Typical Thermal Resistance^(Note 1) ^(Note 2)	R_{θJL} R_{θJA}	18 150					°C/W
Operating Junction Temperature Range	T _J	-55 to +150					°C
Storage Temperature Range	T _{STG}	-55 to +150					°C

NOTES:

1. Mounted on a FR4 PCB, single-sided copper, with 48cm² copper pad area
2. Mounted on a FR4 PCB, single-sided copper, standard footprint
3. Short duration pulse test used to minimize self-heating effect

SB12AFC ~ SB16AFC Series

TYPICAL CHARACTERISTIC CURVES




Fig.1 Forward Current Derating Curve




Fig.2 Typical Junction Capacitance




Fig.3 Typical Forward Characteristics




Fig.4 Typical Forward Characteristics




Fig.5 Typical Reverse Characteristics




Fig.6 Typical Reverse Characteristics




Fig.7 Operating Temperature Derating Curve




SB12AFC ~ SB16AFC Series

Part No. Packing Code Version

Part No. Packing Code	Package Type	Packing Type	Marking	Version
SB12AFC_R1_00001	SMAF-C	3K pcs / 7" reel	SB12	Halogen free
SB13AFC_R1_00001	SMAF-C	3K pcs / 7" reel	SB13	Halogen free
SB14AFC_R1_00001	SMAF-C	3K pcs / 7" reel	SB14	Halogen free
SB15AFC_R1_00001	SMAF-C	3K pcs / 7" reel	SB15	Halogen free
SB16AFC_R1_00001	SMAF-C	3K pcs / 7" reel	SB16	Halogen free

Packaging Information & Mounting Pad Layout





SB12AFC ~ SB16AFC Series

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.