





APPROVED: _____
DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	4/8/05	



SPECIFICATIONS:

Material:
Insulator: Nylon 66, rated UL 94V-2
Insulator color: White
Contacts: Brass

Plating:
Tin over Copper underplate overall

Electrical:
Operating voltage: 250 VAC max
Current rating: 3 Amps max
Dielectric withstanding voltage: 1,500 VAC for 1 minute
Temperature Rating:
Operating temperature: -40°C to +105°C
Environmental:
Lead free, RoHS compliant



Positions: 2 thru 20

A = .100 [2.54] x No. of Positions

B = .100 [2.54] x No. of Spaces

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED
INCHES HOLES
.X ± .10 Ø.X ± .10
.XX ± .020 Ø.XX ± .015
.XXX ± .015 Ø.XXX ± .010

APPROVALS		DATE
DRAWN	SS	4/8/05
CHECKED		
APPROVED		

ADAM TECH

909 Rahway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

TITLE
.100 [2.54] LOCKING HEADER
RIGHT ANGLE, PCB

SIZE	PART NO.	REV.
X	LHA-XX-TRA	-
REF:	S00123T	SCALE: NTS
SHEET 1 OF 1		