



Manage this device with  
Digi Remote Manager

# DIGI EX15

Branch connectivity in a compact, affordable, all-in-one solution

Digi EX15 LTE cellular extenders offer gigabit Ethernet and Wi-Fi connectivity for retailers and other organizations that cannot tolerate network downtime and the negative impact on revenue streams and brand reputation.

A suite of upgradeable Digi CORE® plug-in LTE modems lets users select the cellular speeds that best fit their business requirements, including LTE Cat 4, LTE-Advanced Cat 6 and Cat 11 for data-intensive applications, and LTE-Advanced Pro Cat 18 for critical communications.

Combine a Digi EX15 with a dedicated wireline connection to ensure dual ISP connectivity, maximum uptime and complete business continuity for devices that must be “always on,” such as mobile kiosks, digital signs and POS systems.

You can use Digi EX15 for primary LTE connectivity, in addition to dual-connectivity/failover. Additionally, the serial port can provide out-of-band (OOB) management for remote, off-premise equipment.

Digi device management applications provide easy setup, configuration and support for Digi devices. **Digi Remote Manager®** offers secure, web-based device management for network visibility and control over your Digi enterprise routers and gateways after deployment.

For fast and easy installations, a site survey battery, PoE injector and mounting accessories are included for proper placement based on optimal signal strength.

## FEATURES AND BENEFITS

- LTE-certified Digi CORE® plug-in modem
- Scalable cellular technology allows you to match speeds to applications and future proof your network
- Optimized connectivity to any Ethernet device
- Battery pack for site survey to identify optimal signal strength placement
- Multiple mounting options and accessories
- Serial port for remote, out-of-band management
- Securely deploy, monitor and control devices with Digi Remote Manager®
- Zero-touch provisioning and cloud management

## RELATED PRODUCTS



Digi 6310-DX



Digi 6330-MX



Digi CORE® plug-in  
LTE modem




Digi IX14



Digi Remote  
Manager®


## APPLICATION EXAMPLE



| SPECIFICATIONS                     |                                                                                                                                                                                                                           | DIGI® EX15 |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| CELLULAR CONNECTIVITY              |                                                                                                                                                                                                                           |            |
| DIGI CORE® PLUG-IN LTE MODEMS      | LTE Cat 4 (US): B2, B4, B5, B12, B13; 3G: B2, B5; Transfer rate (max): 150 Mbps down, 50 Mbps up                                                                                                                          |            |
|                                    | LTE Cat 4 (EU): B1, B3, B7, B8, B20; 3G: B1, B8; 2G: B3, B8; Transfer rate (max): 150 Mbps, 50 Mbps up                                                                                                                    |            |
|                                    | LTE-A Cat 6 (GLB): B1, B2, B3, B4, B5, B7, B8, B12, B13, B20, B25, B26, B29, B30, B41; WCDMA: B1, B2, B3, B4, B5, B8; Transfer rate (max): 300 Mbps, 50 Mbps up                                                           |            |
|                                    | LTE-A Cat 11 (GLB): LTE FDD: B1, B2, B3, B4, B5, B7, B8, B12, B13, B17, B20, B25, B26, B29, B30, B66; LTE TDD: B38, B40, B41; 3G: B1, B2, B4, B5, B8; Transfer rate (max): 600 Mbps, 75 Mbps up                           |            |
|                                    | LTE-A Pro Cat 18 (GLB): LTE FDD: B1, B2, B3, B4, B5, B7, B8, B12, B13, B17, B20, B25, B26, B29, B30, B66; LTE TDD: B38, B39, B40, B41; 3G: B1, B2, B4, B5, B8; Transfer rate (max): 1.2 Gbps down, 150 Mbps up per module |            |
| CONNECTORS                         | (2) 50 Ω SMA (center pin: female)                                                                                                                                                                                         |            |
| SIM SLOTS                          | (2) Mini-SIM (2FF); software selectable and hardware switchable                                                                                                                                                           |            |
| SOFTWARE AND MANAGEMENT            |                                                                                                                                                                                                                           |            |
| REMOTE MANAGEMENT                  | Digi Remote Manager®; SNMP v3 (user installed/managed), encrypted SMS                                                                                                                                                     |            |
| LOCAL MANAGEMENT                   | WebUI (HTTP/HTTPS); CLI (SSH, serial port)                                                                                                                                                                                |            |
| PROTOCOLS                          | RIP, RIPng, OSPFv2, OSPFv3, BGP, Babel, IS-IS                                                                                                                                                                             |            |
| MANAGEMENT / TROUBLESHOOTING TOOLS | FTP client, SCP; protocol analyzer with PCAP for Wireshark; event logging with syslog and SMTP client; NTP/SNTP                                                                                                           |            |
| MEMORY                             | 256 MB RAM, 512 MB flash                                                                                                                                                                                                  |            |
| ETHERNET                           |                                                                                                                                                                                                                           |            |
| PORTS                              | (2) RJ-45; 10/100/1000 Mbps (auto-sensing)                                                                                                                                                                                |            |
| WI-FI (OPTIONAL)                   |                                                                                                                                                                                                                           |            |
| CONNECTIVITY                       | 2 x 2 MIMO 2.4/5 GHz: 802.11 b/g/n 2.4 GHz; 802.11 n/a/ac 5 GHz                                                                                                                                                           |            |
| SERIAL                             |                                                                                                                                                                                                                           |            |
| PORTS                              | (1) RS-232 (RJ-45)                                                                                                                                                                                                        |            |
| PHYSICAL                           |                                                                                                                                                                                                                           |            |
| DIMENSIONS (L x W x H)             | 142 mm x 128 mm x 31 mm (5.6 in x 5.0 in x 1.2 in)                                                                                                                                                                        |            |
| WEIGHT                             | 0.2 kg (7.0 oz)                                                                                                                                                                                                           |            |
| STATUS LEDs                        | LAN (link = solid, flashing = act), WAN (link = solid, flashing = act), LTE, 5 signal, SIM 1 and 2 LEDs                                                                                                                   |            |
| ENCLOSURE                          | Plastic                                                                                                                                                                                                                   |            |
| POWER REQUIREMENTS                 |                                                                                                                                                                                                                           |            |
| POWER INPUT                        | 18 VDC 1 A                                                                                                                                                                                                                |            |
| OTHER                              | includes PSU, antennas, and remote mounting kit: temporary battery, passive PoE injector, mounting bracket and accessories                                                                                                |            |
| ENVIRONMENTAL                      |                                                                                                                                                                                                                           |            |
| OPERATING TEMPERATURE              | 0° C to 40° C (32° F to 104° F)                                                                                                                                                                                           |            |
| RELATIVE HUMIDITY                  | 5% to 95% (non-condensing)                                                                                                                                                                                                |            |
| APPROVALS                          |                                                                                                                                                                                                                           |            |
| CELLULAR                           | PTCRB; US: AT&T, Verizon; Canada; Europe                                                                                                                                                                                  |            |
| EMISSIONS / IMMUNITY               | FCC Part 15, Subpart B, Class A; CE, RCM; CAN ICES-3(B)/NMB-3(B)                                                                                                                                                          |            |
| WARRANTY                           |                                                                                                                                                                                                                           |            |
| PRODUCT WARRANTY                   | 3-year*                                                                                                                                                                                                                   |            |

\*Standard 3-year warranty upgradeable to 5 years with purchase of a Digi Remote Manager Premier 5-year subscription applicable to the product purchased only at the time of product purchase and with product registration at that time in Digi Remote Manager.

PRODUCT IMAGES



DIGI REMOTE MANAGER®



Digi Remote Manager is the technology platform that brings networks to the next level, allowing networks — and the people who manage them — to work smarter. With Digi Remote Manager you can transform a multitude of dispersed IoT devices into a dynamic, intelligent network. Now you can easily deploy, monitor and diagnose thousands of mission-critical devices from a single point of command — on your desktop, tablet or phone. All the while, its software-defined security diligently safeguards your entire Digi ecosystem.

Learn more at [www.digi.com/digi-remote-manager](http://www.digi.com/digi-remote-manager)

CAPABILITIES

- Activate, monitor and diagnose your mission-critical devices from a single point of command and control — on your desktop or mobile app
- Schedule key operations — including firmware updates and file management — on a single device or on a group of devices, keeping your network functionality up-to-date and maintaining compliance standards
- Manage edge devices out-of-band via console terminal access
- Keep tabs on device health and connectivity across device deployments of any size
- Create detailed reports and enable real-time alerts for specified conditions
- Integrate device data through open APIs to gain deeper insights and control with third-party applications
- Report and alert on performance statistics, including connection history, signal quality, latency, data usage and packet loss

INFRASTRUCTURE

- Hosted in a commercial-grade cloud server environment that meets SOC 1®, SOC 2® and SOC 3® standards
- Superior availability, operating to 99.9% or greater
- Open APIs available to support application development

SECURITY

- More than 175 security controls in place to protect your data
- Member of the Center for Internet Security® (CIS®)
- Enables compliance with security frameworks like ISO27002, HIPAA, NIST and more
- Earned Skyhigh's CloudTrust™ Program highest rating of Enterprise-Ready

| PART NUMBERS    | DIGI REMOTE MANAGER®                               |
|-----------------|----------------------------------------------------|
| DIGI-RM-STD-1YR | Digi Remote Manager Standard - 1-year subscription |
| DIGI-RM-PRM-1YR | Digi Remote Manager Premier - 1-year subscription  |
| DIGI-RM-PRM-3YR | Digi Remote Manager Premier - 3-year subscription  |
| DIGI-RM-PRM-5YR | Digi Remote Manager Premier - 5-year subscription  |

| PART NUMBERS      | DIGI® EX15                                                                                                                                   |
|-------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| ASB-EX15-XX04-OUS | Digi EX15: 2-port GigE; RJ-45, RS-232, No Wi-Fi; LTE / HSPA+ Cat 4; Cellular certifications: PTCRB, AT&T, Verizon, US, Canada                |
| ASB-EX15-XXE4-GLB | Digi EX15: 2-port GigE; RJ-45, RS-232, No Wi-Fi; LTE / HSPA+ Cat 4; Cellular certifications: PTCRB, Europe                                   |
| ASB-EX15-XX06-GLB | Digi EX15: 2-port GigE; RJ-45, RS-232, No Wi-Fi; LTE-A / HSPA+ Cat 6; Cellular certifications: PTCRB, AT&T, Verizon, US, Canada, Europe      |
| ASB-EX15-XX11-OUS | Digi EX15: 2-port GigE; RJ-45, RS-232, No Wi-Fi; LTE-A / HSPA+ Cat 11; Cellular certifications: PTCRB, AT&T, Verizon, US, Canada             |
| ASB-EX15-XX11-GLB | Digi EX15: 2-port GigE; RJ-45, RS-232, No Wi-Fi; LTE-A / HSPA+ Cat 11; Cellular certifications: PTCRB, AT&T, Verizon, US, Canada, Europe     |
| ASB-EX15-XC18-GLB | Digi EX15: 2-port GigE; RJ-45, RS-232, No Wi-Fi; LTE-A Pro / HSPA+ Cat 18; Cellular certifications: PTCRB, AT&T, Verizon, US, Canada, Europe |
| ASB-EX15-WX04-OUS | Digi EX15: 2-port GigE; RJ-45, RS-232, Wi-Fi; LTE / HSPA+ Cat 4; Cellular certifications: PTCRB, AT&T, Verizon, US, Canada                   |
| ASB-EX15-WXE4-GLB | Digi EX15: 2-port GigE; RJ-45, RS-232, Wi-Fi; LTE / HSPA+ Cat 4; Cellular certifications: PTCRB, Europe                                      |
| ASB-EX15-WX06-GLB | Digi EX15: 2-port GigE; RJ-45, RS-232, Wi-Fi; LTE-A / HSPA+ Cat 6; Cellular certifications: PTCRB, AT&T, Verizon, US, Canada, Europe         |
| ASB-EX15-WX11-OUS | Digi EX15: 2-port GigE; RJ-45, RS-232, Wi-Fi; LTE-A / HSPA+ Cat 11; Cellular certifications: PTCRB, AT&T, Verizon, US, Canada                |
| ASB-EX15-WX11-GLB | Digi EX15: 2-port GigE; RJ-45, RS-232, Wi-Fi; LTE-A / HSPA+ Cat 11; Cellular certifications: PTCRB, AT&T, Verizon, US, Canada, Europe        |
| ASB-EX15-WC18-GLB | Digi EX15: 2-port GigE; RJ-45, RS-232, Wi-Fi; LTE-A Pro / HSPA+ Cat 18; Cellular certifications: PTCRB, AT&T, Verizon, US, Canada, Europe    |

| PART NUMBERS      | DIGI CORE® PLUG-IN LTE MODEMS                                                                                            |
|-------------------|--------------------------------------------------------------------------------------------------------------------------|
| ASB-1002-CM04-OUS | Digi CORE plug-in LTE modem; LTE / HSPA+ Cat 4; Cellular certifications: PTCRB, AT&T, Verizon, Canada                    |
| ASB-1002-CME4-GLB | Digi CORE plug-in LTE modem; LTE / HSPA+ Cat 4; Cellular certifications: PTCRB, RED, Europe                              |
| ASB-1002-CM06-GLB | Digi CORE plug-in LTE modem; LTE-A / HSPA+ Cat 6; Cellular certifications: PTCRB, RED, AT&T, Verizon, Canada, Europe     |
| ASB-1003-CM11-GLB | Digi CORE plug-in LTE modem; LTE-A / HSPA+ Cat 11; Cellular certifications: PTCRB, RED, AT&T, Verizon, Canada, Europe    |
| ASB-1003-CM18-GLB | Digi CORE plug-in LTE modem; LTE-A Pro / HSPA+ Cat 18; Cellular certifications: PTCRB, AT&T, Verizon, US, Canada, Europe |

| PART NUMBERS | ACCESSORIES                                                                                                                                                                          |
|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 450061       | 18 V PSU power supply with barrel jack connector (replacement)                                                                                                                       |
| 500157       | Cable assembly passive POE power injector, white 2.1 mm barrel connector (replacement)                                                                                               |
| 560083       | Temporary site survey battery pack, 9 V with 152.4 mm power lead, 2.1 mm barrel connector (replacement)                                                                              |
| 170011       | (1) Antenna extender: 48 mm circle antenna magnetic base (base connector: SMA jack); cable: low loss CLF; 50 cm length with SMA plug (replacement for optional Wi-Fi enabled models) |
| 170017       | (2) Cellular antenna (replacement)                                                                                                                                                   |

\*Digi EX15 FirstNet® models are only available through AT&T®, FirstNet® and FirstNet Ready™ are registered trademarks and service marks of the First Responder Network Authority.

**DIGI SERVICE AND SUPPORT** / You can purchase with confidence knowing that Digi is always available to serve you with expert technical support and our industry leading warranty. For detailed information visit [www.digi.com/support](http://www.digi.com/support).

© 1996-2021 Digi International Inc. All rights reserved.  
All trademarks are the property of their respective owners.

**DIGI INTERNATIONAL WORLDWIDE HQ**  
877-912-3444 / 952-912-3444 / [www.digi.com](http://www.digi.com)

**DIGI INTERNATIONAL JAPAN**  
+81-3-5428-0261 / [www.digi-intl.co.jp](http://www.digi-intl.co.jp)

**DIGI INTERNATIONAL GERMANY**  
+49-89-540-428-0

**DIGI INTERNATIONAL SINGAPORE**  
+65-6213-5380

**DIGI INTERNATIONAL CHINA**  
+86-21-50492199 / [www.digi.com.cn](http://www.digi.com.cn)