



DC POWER CONNECTORS: KLDLX-P Series

Locking DC Power Plug

Product Features

- 2.0mm and 2.5mm Pin Options
- Locking ring
- Solder Eyelets
- Locks when used with the KLDLX & KLDPLX Series

Performance Specifications

Materials and Finish

- Barrel:** Brass, Nickel Plated
- Coupling Ring:** Brass, Nickel Plated
- Insulator:** PBT
- Rear Cover:** ABS

Electrical Characteristics

- Insulation Resistance:** 100 Megohms Min. at 500V DC
- Contact Resistance:** 30 milliohms Max.
- Dielectric Withstanding Voltage:** 500V for 1 Minute
- Rated Current:** 5A
- Rated Voltage:** 24V DC

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

Generated Part Number

Part Number Builder

	-		-		-		-	
Series		Product Type		Diameter		Barrel Thread		Barrel Length

Series

KLDLX-P - Locking DC Power Plug

Product Type

0202 - 2mm options

Diameter

A - 2.0mm Center Pin Diameter

B - 2.5mm Center Pin Diameter

Barrel Thread

M8 - M8 thread

Barrel length

Blank - 5.7mm barrel length

LB - 8.0mm barrel length (Contact Kycon for more Information)

Contact Kycon For Other Options

KLDLX-P Series

