

PC 95/35 LT



Sample image

Order symbol: PC 95/35 LT

Product nbr: 6012931

UL Code: 6412931

UL Name: UL PC 95/35 LT

Description: Enclosure. PC

Remarks: Smoked transparent cover

Including: Base with PUR gasket. screws for mounting plate/DIN-rail and cover with polyamide cover screws.

EAN: 6418074054654

El. number:

- Finland: 3421368
- Denmark: 8212027695
- Sweden: 6012931

Technical drawing of a 100x100x35-50 mm aluminum extrusion profile. The drawing includes three views: a top view, a side view, and a cross-sectional view. The top view shows a square profile with a central slot and four corner slots. The side view shows the profile's height and width. The cross-sectional view shows the internal structure of the profile, including the central slot and corner slots. Dimensions are provided in millimeters.

Top View Dimensions:

- Overall width: 100 mm
- Overall height: 100 mm
- Inner width: 89 mm
- Inner height: 89 mm
- Slot width: 45 mm
- Slot height: 65 mm
- Slot depth: 83.5 mm
- Slot width (inner): 65 mm
- Slot height (inner): 32 mm
- Slot depth (inner): 18 mm
- Slot width (inner): 11 mm
- Slot height (inner): 11 mm
- Slot depth (inner): 11 mm

Side View Dimensions:

- Overall width: 100 mm
- Overall height: 100 mm
- Inner width: 89 mm
- Inner height: 89 mm
- Slot width: 45 mm
- Slot height: 65 mm
- Slot depth: 83.5 mm
- Slot width (inner): 65 mm
- Slot height (inner): 32 mm
- Slot depth (inner): 18 mm
- Slot width (inner): 11 mm
- Slot height (inner): 11 mm
- Slot depth (inner): 11 mm

Cross-sectional View Dimensions:

- Overall width: 100 mm
- Overall height: 100 mm
- Inner width: 89 mm
- Inner height: 89 mm
- Slot width: 45 mm
- Slot height: 65 mm
- Slot depth: 83.5 mm
- Slot width (inner): 65 mm
- Slot height (inner): 32 mm
- Slot depth (inner): 18 mm
- Slot width (inner): 11 mm
- Slot height (inner): 11 mm
- Slot depth (inner): 11 mm

Ingress protection (EN 60529):	IP66; IP67;
Impact Resistance (EN 62262):	IK08;
Electrical insulation:	Totally insulated
Halogen free (DIN/VDE 0472, Part 815):	1
UV resistance:	UL 508
Flammability Rating:	UL 746C 5"
Glow Wire Test (IEC 695-2-1) °C:	960 °C
NEMA Class	

Certificates:

Certificate FI 40847