


## HEXFET® Power MOSFET

### Applications


- Brushed motor drive applications
- BLDC motor drive applications
- Battery powered circuits
- Half-bridge and full-bridge topologies
- Synchronous rectifier applications
- Resonant mode power supplies
- OR-ing and redundant power switches
- DC/DC and AC/DC converters
- DC/AC inverters

### Benefits

- Improved gate, avalanche and dynamic dV/dt ruggedness
- Fully characterized capacitance and avalanche SOA
- Enhanced body diode dV/dt and dI/dt capability
- Lead-free




|                          |               |
|--------------------------|---------------|
| $V_{DS}$                 | <b>40V</b>    |
| $R_{DS(on)}$ <b>typ.</b> | <b>0.97mΩ</b> |
| <b>max.</b>              | <b>1.2mΩ</b>  |
| $I_D$ (Silicon Limited)  | <b>426A ①</b> |
| $I_D$ (Package Limited)  | <b>195A</b>   |




|          |          |          |
|----------|----------|----------|
| <b>G</b> | <b>D</b> | <b>S</b> |
| Gate     | Drain    | Source   |

| Base Part Number | Package Type | Standard Pack      |          | Orderable Part Number |
|------------------|--------------|--------------------|----------|-----------------------|
|                  |              | Form               | Quantity |                       |
| IRFSL7430PbF     | TO-262       | Tube               | 50       | IRFSL7430PbF          |
| IRFS7430PbF      | D2-Pak       | Tube               | 50       | IRFS7430PbF           |
|                  |              | Tape and Reel Left | 800      | IRFS7430TRLPbF        |



**Fig 1.** Typical On-Resistance vs. Gate Voltage



**Fig 2.** Maximum Drain Current vs. Case Temperature

# Absolute Maximum Ratings

| Symbol                          | Parameter                                                           | Max.         | Units |
|---------------------------------|---------------------------------------------------------------------|--------------|-------|
| $I_D @ T_C = 25^\circ\text{C}$  | Continuous Drain Current, $V_{GS} @ 10\text{V}$ (Silicon Limited)   | 426①         | A     |
| $I_D @ T_C = 100^\circ\text{C}$ | Continuous Drain Current, $V_{GS} @ 10\text{V}$ (Silicon Limited)   | 301①         |       |
| $I_D @ T_C = 25^\circ\text{C}$  | Continuous Drain Current, $V_{GS} @ 10\text{V}$ (Wire Bond Limited) | 195          |       |
| $I_{DM}$                        | Pulsed Drain Current ②                                              | 1524         |       |
| $P_D @ T_C = 25^\circ\text{C}$  | Maximum Power Dissipation                                           | 375          | W     |
|                                 | Linear Derating Factor                                              | 2.5          | W/°C  |
| $V_{GS}$                        | Gate-to-Source Voltage                                              | $\pm 20$     | V     |
| $T_J$                           | Operating Junction and                                              | -55 to + 175 | °C    |
| $T_{STG}$                       | Storage Temperature Range                                           |              |       |
|                                 | Soldering Temperature, for 10 seconds (1.6mm from case)             | 300          |       |

# Avalanche Characteristics

|                              |                                 |                           |    |
|------------------------------|---------------------------------|---------------------------|----|
| $E_{AS}$ (Thermally limited) | Single Pulse Avalanche Energy ③ | 760                       | mJ |
| $E_{AS}$ (Thermally limited) | Single Pulse Avalanche Energy ④ | 1452                      |    |
| $I_{AR}$                     | Avalanche Current ②             | See Fig. 15, 16, 22a, 22b | A  |
| $E_{AR}$                     | Repetitive Avalanche Energy ②   |                           | mJ |

# Thermal Resistance

| Symbol          | Parameter                                       | Typ. | Max. | Units |
|-----------------|-------------------------------------------------|------|------|-------|
| $R_{\theta JC}$ | Junction-to-Case ⑤                              | —    | 0.40 | °C/W  |
| $R_{\theta JA}$ | Junction-to-Ambient (PCB Mount, steady-state) ⑥ | —    | 40   |       |

# Static @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

| Symbol                          | Parameter                            | Min. | Typ.  | Max. | Units | Conditions                                                               |
|---------------------------------|--------------------------------------|------|-------|------|-------|--------------------------------------------------------------------------|
| $V_{(BR)DSS}$                   | Drain-to-Source Breakdown Voltage    | 40   | —     | —    | V     | $V_{GS} = 0\text{V}$ , $I_D = 250\mu\text{A}$                            |
| $\Delta V_{(BR)DSS}/\Delta T_J$ | Breakdown Voltage Temp. Coefficient  | —    | 0.014 | —    | V/°C  | Reference to $25^\circ\text{C}$ , $I_D = 1.0\text{mA}$                   |
| $R_{DS(on)}$                    | Static Drain-to-Source On-Resistance | —    | 0.97  | 1.2  | mΩ    | $V_{GS} = 10\text{V}$ , $I_D = 100\text{A}$ ⑦                            |
|                                 |                                      | —    | 1.2   | —    |       | $V_{GS} = 6.0\text{V}$ , $I_D = 50\text{A}$ ⑧                            |
| $V_{GS(th)}$                    | Gate Threshold Voltage               | 2.2  | —     | 3.9  | V     | $V_{DS} = V_{GS}$ , $I_D = 250\mu\text{A}$                               |
| $I_{DSS}$                       | Drain-to-Source Leakage Current      | —    | —     | 1.0  | μA    | $V_{DS} = 40\text{V}$ , $V_{GS} = 0\text{V}$                             |
|                                 |                                      | —    | —     | 150  |       | $V_{DS} = 40\text{V}$ , $V_{GS} = 0\text{V}$ , $T_J = 125^\circ\text{C}$ |
| $I_{GSS}$                       | Gate-to-Source Forward Leakage       | —    | —     | 100  | nA    | $V_{GS} = 20\text{V}$                                                    |
|                                 | Gate-to-Source Reverse Leakage       | —    | —     | -100 |       | $V_{GS} = -20\text{V}$                                                   |
| $R_G$                           | Internal Gate Resistance             | —    | 2.1   | —    | Ω     |                                                                          |

# Notes:

- ① Calculated continuous current based on maximum allowable junction temperature. Bond wire current limit is 195A. Note that current limitations arising from heating of the device leads may occur with some lead mounting arrangements. (Refer to AN-1140)
- ② Repetitive rating; pulse width limited by max. junction temperature.
- ③ Limited by  $T_{Jmax}$ , starting  $T_J = 25^\circ\text{C}$ ,  $L = 0.15\text{mH}$ ,  $R_G = 50\Omega$ ,  $I_{AS} = 100\text{A}$ ,  $V_{GS} = 10\text{V}$ .
- ④  $I_{SD} \leq 100\text{A}$ ,  $di/dt \leq 990\text{A}/\mu\text{s}$ ,  $V_{DD} \leq V_{(BR)DSS}$ ,  $T_J \leq 175^\circ\text{C}$ .
- ⑤ Pulse width  $\leq 400\mu\text{s}$ ; duty cycle  $\leq 2\%$ .
- ⑥  $C_{OSS}$  eff. (TR) is a fixed capacitance that gives the same charging time as  $C_{OSS}$  while  $V_{DS}$  is rising from 0 to 80%  $V_{DSS}$ .
- ⑦  $C_{OSS}$  eff. (ER) is a fixed capacitance that gives the same energy as  $C_{OSS}$  while  $V_{DS}$  is rising from 0 to 80%  $V_{DSS}$ .
- ⑧  $R_\theta$  is measured at  $T_J$  approximately  $90^\circ\text{C}$ .
- ⑨ Limited by  $T_{Jmax}$  starting  $T_J = 25^\circ\text{C}$ ,  $L = 1\text{mH}$ ,  $R_G = 50\Omega$ ,  $I_{AS} = 54\text{A}$ ,  $V_{GS} = 10\text{V}$ .
- ⑩ When mounted on 1" square PCB (FR-4 or G-10 Material). For recommended footprint and soldering techniques refer to application note #AN-994. <http://www.irf.com/technical-info/appnotes/an-994.pdf>

**Dynamic @  $T_J = 25^\circ\text{C}$  (unless otherwise specified)**

| Symbol                      | Parameter                                     | Min. | Typ.  | Max. | Units | Conditions                                                         |
|-----------------------------|-----------------------------------------------|------|-------|------|-------|--------------------------------------------------------------------|
| $g_{fs}$                    | Forward Transconductance                      | 150  | —     | —    | S     | $V_{DS} = 10\text{V}$ , $I_D = 100\text{A}$                        |
| $Q_g$                       | Total Gate Charge                             | —    | 300   | 460  | nC    | $I_D = 100\text{A}$                                                |
| $Q_{gs}$                    | Gate-to-Source Charge                         | —    | 77    | —    |       | $V_{DS} = 20\text{V}$                                              |
| $Q_{gd}$                    | Gate-to-Drain ("Miller") Charge               | —    | 98    | —    |       | $V_{GS} = 10\text{V}$ ⑤                                            |
| $Q_{sync}$                  | Total Gate Charge Sync. ( $Q_g - Q_{gd}$ )    | —    | 202   | —    |       | $I_D = 100\text{A}$ , $V_{DS} = 0\text{V}$ , $V_{GS} = 10\text{V}$ |
| $t_{d(on)}$                 | Turn-On Delay Time                            | —    | 32    | —    | ns    | $V_{DD} = 20\text{V}$                                              |
| $t_r$                       | Rise Time                                     | —    | 105   | —    |       | $I_D = 30\text{A}$                                                 |
| $t_{d(off)}$                | Turn-Off Delay Time                           | —    | 160   | —    |       | $R_G = 2.7\Omega$                                                  |
| $t_f$                       | Fall Time                                     | —    | 100   | —    |       | $V_{GS} = 10\text{V}$ ⑤                                            |
| $C_{iss}$                   | Input Capacitance                             | —    | 14240 | —    | pF    | $V_{GS} = 0\text{V}$                                               |
| $C_{oss}$                   | Output Capacitance                            | —    | 2130  | —    |       | $V_{DS} = 25\text{V}$                                              |
| $C_{rss}$                   | Reverse Transfer Capacitance                  | —    | 1460  | —    |       | $f = 1.0\text{ MHz}$                                               |
| $C_{oss \text{ eff. (ER)}}$ | Effective Output Capacitance (Energy Related) | —    | 2605  | —    |       | $V_{GS} = 0\text{V}$ , $V_{DS} = 0\text{V to } 32\text{V}$ ⑦       |
| $C_{oss \text{ eff. (TR)}}$ | Effective Output Capacitance (Time Related)   | —    | 2920  | —    |       | $V_{GS} = 0\text{V}$ , $V_{DS} = 0\text{V to } 32\text{V}$ ⑥       |

**Diode Characteristics**

| Symbol    | Parameter                                 | Min. | Typ. | Max.  | Units | Conditions                                                                                     |
|-----------|-------------------------------------------|------|------|-------|-------|------------------------------------------------------------------------------------------------|
| $I_S$     | Continuous Source Current<br>(Body Diode) | —    | —    | 426 ① | A     | MOSFET symbol showing the integral reverse p-n junction diode.                                 |
| $I_{SM}$  | Pulsed Source Current<br>(Body Diode) ②   | —    | —    | 1524  | A     |                                                                                                |
| $V_{SD}$  | Diode Forward Voltage                     | —    | 0.86 | 1.2   | V     | $T_J = 25^\circ\text{C}$ , $I_S = 100\text{A}$ , $V_{GS} = 0\text{V}$ ③                        |
| $dv/dt$   | Peak Diode Recovery ④                     | —    | 2.7  | —     | V/ns  | $T_J = 175^\circ\text{C}$ , $I_S = 100\text{A}$ , $V_{DS} = 40\text{V}$                        |
| $t_{rr}$  | Reverse Recovery Time                     | —    | 52   | —     | ns    | $T_J = 25^\circ\text{C}$ $V_R = 34\text{V}$ ,<br>$T_J = 125^\circ\text{C}$ $I_F = 100\text{A}$ |
| $Q_{rr}$  | Reverse Recovery Charge                   | —    | 97   | —     | nC    | $T_J = 25^\circ\text{C}$ $di/dt = 100\text{A}/\mu\text{s}$ ⑤<br>$T_J = 125^\circ\text{C}$      |
| $I_{RRM}$ | Reverse Recovery Current                  | —    | 2.3  | —     | A     | $T_J = 25^\circ\text{C}$                                                                       |






Fig 3. Typical Output Characteristics




Fig 4. Typical Output Characteristics




Fig 5. Typical Transfer Characteristics




Fig 6. Normalized On-Resistance vs. Temperature




Fig 7. Typical Capacitance vs. Drain-to-Source Voltage







Fig 8. Typical Gate Charge vs. Gate-to-Source Voltage




**Fig 9.** Typical Source-Drain Diode Forward Voltage




**Fig 10.** Maximum Safe Operating Area




**Fig 11.** Drain-to-Source Breakdown Voltage




**Fig 12.** Typical  $C_{OSS}$  Stored Energy




**Fig 13.** Typical On-Resistance vs. Drain Current



**Fig 14.** Maximum Effective Transient Thermal Impedance, Junction-to-Case



**Fig 15.** Avalanche Current vs. Pulsewidth



**Fig 16.** Maximum Avalanche Energy vs. Temperature






**Notes on Repetitive Avalanche Curves , Figures 15, 16:**  
(For further info, see AN-1005 at [www.irf.com](http://www.irf.com))



1. Avalanche failures assumption:  
Purely a thermal phenomenon and failure occurs at a temperature far in excess of  $T_{jmax}$ . This is validated for every part type.
2. Safe operation in Avalanche is allowed as long as  $T_{jmax}$  is not exceeded.
3. Equation below based on circuit and waveforms shown in Figures 16a, 16b.
4.  $P_{D(ave)}$  = Average power dissipation per single avalanche pulse.
5. BV = Rated breakdown voltage (1.3 factor accounts for voltage increase during avalanche).
6.  $I_{av}$  = Allowable avalanche current.
7.  $\Delta T$  = Allowable rise in junction temperature, not to exceed  $T_{jmax}$  (assumed as 25°C in Figure 15, 16).  
 $t_{av}$  = Average time in avalanche.  
 $D$  = Duty cycle in avalanche =  $t_{av} \cdot f$   
 $Z_{thJC}(D, t_{av})$  = Transient thermal resistance, see Figures 14)

$$P_{D(ave)} = 1/2 (1.3 \cdot BV \cdot I_{av}) = \Delta T / Z_{thJC}$$


$$I_{av} = 2\Delta T / [1.3 \cdot BV \cdot Z_{th}]$$

$$E_{AS(AR)} = P_{D(ave)} \cdot t_{av}$$



**Fig 17.** Threshold Voltage vs. Temperature

**Fig. 18 -** Typical Recovery Current vs.  $di_F/dt$ 

**Fig. 19 -** Typical Recovery Current vs.  $di_F/dt$ 

**Fig. 20 -** Typical Stored Charge vs.  $di_F/dt$ 

**Fig. 21 -** Typical Stored Charge vs.  $di_F/dt$




**Fig 22. Peak Diode Recovery dv/dt Test Circuit for N-Channel HEXFET® Power MOSFETs**




**Fig 22a. Unclamped Inductive Test Circuit**




**Fig 22b. Unclamped Inductive Waveforms**




**Fig 23a. Switching Time Test Circuit**



**Fig 23b. Switching Time Waveforms**



**Fig 24a. Gate Charge Test Circuit**




**Fig 24b. Gate Charge Waveform**



## D<sup>2</sup>Pak (TO-263AB) Package Outline

Dimensions are shown in millimeters (inches)



| SYMBOL | DIMENSIONS  |       |          |      | NOTES |
|--------|-------------|-------|----------|------|-------|
|        | MILLIMETERS |       | INCHES   |      |       |
|        | MIN.        | MAX.  | MIN.     | MAX. |       |
| A      | 4.06        | 4.83  | .160     | .190 | 5     |
| A1     | 0.00        | 0.254 | .000     | .010 |       |
| b      | 0.51        | 0.99  | .020     | .039 |       |
| b1     | 0.51        | 0.89  | .020     | .035 |       |
| b2     | 1.14        | 1.78  | .045     | .070 |       |
| b3     | 1.14        | 1.73  | .045     | .068 | 5     |
| c      | 0.38        | 0.74  | .015     | .029 | 5     |
| c1     | 0.38        | 0.58  | .015     | .023 |       |
| c2     | 1.14        | 1.65  | .045     | .065 |       |
| D      | 8.38        | 9.65  | .330     | .380 | 3     |
| D1     | 6.86        | —     | .270     | —    | 4     |
| E      | 9.65        | 10.67 | .380     | .420 | 3,4   |
| E1     | 6.22        | —     | .245     | —    | 4     |
| e      | 2.54 BSC    |       | .100 BSC |      | 4     |
| H      | 14.61       | 15.88 | .575     | .625 |       |
| L      | 1.78        | 2.79  | .070     | .110 |       |
| L1     | —           | 1.68  | —        | .066 |       |
| L2     | —           | 1.78  | —        | .070 |       |
| L3     | 0.25 BSC    |       | .010 BSC |      |       |

### NOTES:

- DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994
- DIMENSIONS ARE SHOWN IN MILLIMETERS [INCHES].
- DIMENSION D & E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED 0.127 [0.005"] PER SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTMOST EXTREMES OF THE PLASTIC BODY AT DATUM H.
- THERMAL PAD CONTOUR OPTIONAL WITHIN DIMENSION E, L1, D1 & E1.
- DIMENSION b1, b3 AND c1 APPLY TO BASE METAL ONLY.
- DATUM A & B TO BE DETERMINED AT DATUM PLANE H.
- CONTROLLING DIMENSION: INCH.
- OUTLINE CONFORMS TO JEDEC OUTLINE TO-263AB.

### LEAD ASSIGNMENTS

#### DIODES

- ANODE (TWO DIE) / OPEN (ONE DIE)
- CATHODE
- ANODE

#### HEXFET

- GATE
- DRAIN
- SOURCE


#### IGBTs, CoPACK

- GATE
- COLLECTOR
- EMITTER


## D<sup>2</sup>Pak (TO-263AB) Part Marking Information

EXAMPLE: THIS IS AN IRF530S WITH  
LOT CODE 8024  
ASSEMBLED ON WW 02, 2000  
IN THE ASSEMBLY LINE "L"

Note: "P" in assembly line position  
indicates "Lead - Free"




OR



Note: For the most current drawing please refer to IR website at <http://www.irf.com/package/>

## TO-262 Package Outline

Dimensions are shown in millimeters (inches)



| SYM-<br>BOL | DIMENSIONS  |       |        |      | NOTES |
|-------------|-------------|-------|--------|------|-------|
|             | MILLIMETERS |       | INCHES |      |       |
|             | MIN.        | MAX.  | MIN.   | MAX. |       |
| A           | 4.06        | 4.83  | .160   | .190 |       |
| a1          | 2.03        | 3.02  | .080   | .119 |       |
| b           | 0.51        | 0.99  | .020   | .039 |       |
| b1          | 0.51        | 0.89  | .020   | .035 | 5     |
| b2          | 1.14        | 1.78  | .045   | .070 |       |
| b3          | 1.14        | 1.73  | .045   | .068 | 5     |
| c           | 0.38        | 0.74  | .015   | .029 |       |
| c1          | 0.38        | 0.58  | .015   | .023 | 5     |
| d           | 1.14        | 1.65  | .045   | .065 |       |
| D           | 8.38        | 9.65  | .330   | .380 | 3     |
| D1          | 6.86        | —     | .270   | —    | 4     |
| E           | 9.65        | 10.67 | .380   | .420 | 3,4   |
| E1          | 6.22        | —     | .245   | —    | 4     |
| e           | 2.54        | BSC   | .100   | BSC  |       |
| L           | 13.46       | 14.10 | .530   | .555 |       |
| L1          | —           | 1.65  | —      | .065 | 4     |
| L2          | 3.56        | 3.71  | .140   | .146 |       |

NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994
2. DIMENSIONS ARE SHOWN IN MILLIMETERS [INCHES].
3. DIMENSION D & E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED 0.127 [0.005"] PER SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTMOST EXTREMES OF THE PLASTIC BODY.
4. THERMAL PAD CONTOUR OPTIONAL WITHIN DIMENSION E, L1, D1 & E1.
5. DIMENSION b1 AND c1 APPLY TO BASE METAL ONLY.
6. CONTROLLING DIMENSION: INCH.
7. - OUTLINE CONFORM TO JEDEC TO-262 EXCEPT A1(max.), b(min.) AND D1(min.) WHERE DIMENSIONS DERIVED THE ACTUAL PACKAGE OUTLINE.

## LEAD ASSIGNMENTS

## IGBTs, CoPACK

- 1.— GATE
- 2.— COLLECTOR
- 3.— EMITTER
- 4.— COLLECTOR

## HEXFET

- 1.- GATE
- 2.- DRAIN
- 3.- SOURCE
- 4.- DRAIN


## DIODES

- 1.- ANODE (TWO DIE) / OPEN (ONE DIE)
2. 4.- CATHODE
- 3.- ANODE


## TO-262 Part Marking Information

EXAMPLE: THIS IS AN IRL3103L  
LOT CODE 1789  
ASSEMBLED ON WW 19, 1997  
IN THE ASSEMBLY LINE "C"

Note: "P" in assembly line position indicates "Lead - Free"




OR



Note: For the most current drawing please refer to IR website at <http://www.irf.com/package/>

# D<sup>2</sup>Pak (TO-263AB) Tape & Reel Information

Dimensions are shown in millimeters (inches)



Note: For the most current drawing please refer to IR website at: <http://www.irf.com/package/>

**Qualification information†**

|                            |                                                            |                                               |
|----------------------------|------------------------------------------------------------|-----------------------------------------------|
| Qualification level        | Industrial<br>(per JEDEC JESD47F <sup>††</sup> guidelines) |                                               |
| Moisture Sensitivity Level | D2Pak                                                      | MSL1<br>(per JEDEC J-STD-020D <sup>††</sup> ) |
|                            | TO-262                                                     | Not applicable                                |
| RoHS compliant             | Yes                                                        |                                               |

† Qualification standards can be found at International Rectifier's web site: <http://www.irf.com/product-info/reliability/>

†† Applicable version of JEDEC standard at the time of product release.

**Revision History**

| Date      | Comment                                                                                                                                                                                                                                                                                                                                                                             |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 11/6/2014 | <ul style="list-style-type: none"> <li>Updated <math>E_{AS}(L=1mH) = 1452mJ</math> on page 2</li> <li>Updated note 9 "Limited by <math>T_{Jmax}</math>, starting <math>T_J = 25^{\circ}C</math>, <math>L = 1mH</math>, <math>R_G = 50\Omega</math>, <math>I_{AS} = 54A</math>, <math>V_{GS} = 10V</math>". on page 2</li> <li>Updated package outline on page 9 &amp; 10</li> </ul> |

International  
 Rectifier

**IR WORLD HEADQUARTERS:** 101 N. Sepulveda Blvd., El Segundo, California 90245, USA  
 To contact International Rectifier, please visit <http://www.irf.com/whoto-call/>

## IMPORTANT NOTICE

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenhheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

For further information on the product, technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies office ([www.infineon.com](http://www.infineon.com)).

## WARNINGS

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.