

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C <sup>(1)</sup>		STORAGE TEMPERATURE RANGE	-10 °C TO 60 °C <sup>(2)</sup>
	VOLTAGE	200 V AC		OPERATING HUMIDITY RANGE	40 % TO 80 %
	CURRENT	3 A		STORAGE HUMIDITY RANGE	40 % TO 70 % <sup>(2)</sup>
SPECIFICATIONS					
ITEM	TEST METHOD		REQUIREMENTS		QT AT
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
MARKING	CONFIRMED VISUALLY.				<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
ELECTRIC CHARACTERISTICS					
CONTACT RESISTANCE	100 mA (DC OR 1000 Hz).		15 mΩ MAX.		<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
INSULATION RESISTANCE	500 V DC		1000 MΩ MIN.		<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
VOLTAGE PROOF	650 V AC FOR 1 min.		NO FLASHOVER OR BREAKDOWN.		<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
MECHANICAL CHARACTERISTICS					
MECHANICAL OPERATION	500 TIMES INSERTIONS AND EXTRACTIONS.		<sup>①</sup> CONTACT RESISTANCE: 15 mΩ MAX. <sup>②</sup> NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
VIBRATION	FREQUENCY 10 TO 55 Hz, AMPLITUDE : 1.5mm, AT 2 h FOR 3 DIRECTIONS.		<sup>①</sup> NO ELECTRICAL DISCONTINUITY OF 1 μs. <sup>②</sup> NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
SHOCK	490 m/s <sup>2</sup> , DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.				<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
ENVIRONMENTAL CHARACTERISTICS					
DAMP HEAT (STEADY STATE)	EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 h.		<sup>①</sup> CONTACT RESISTANCE: 15 mΩ MAX. <sup>②</sup> INSULATION RESISTANCE: 1000 MΩ MIN.		<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -65 → +15 ~ +35 → +125 → +15 +35 °C TIME 30 → 10 ~ 15 → 30 → 10 ~ 15 min UNDER 5 CYCLES.		<sup>③</sup> NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.		<sup>①</sup> CONTACT RESISTANCE: 15 mΩ MAX. <sup>②</sup> NO HEAVY CORROSION.		<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
HYDROGEN SULPHIDE	EXPOSED IN 3 PPM FOR 96 h. (TEST STANDARD: JEIDA 38)				<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
RESISTANCE TO SOLDERING HEAT	1) SOLDER BATH: SOLDER TEMPERATURE, 260±5 °C FOR IMMERSION, DURATION, 10±1s.		NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.		<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
	2) SOLDERING IRONS : 350 °C, FOR 3 s				<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
SOLDERABILITY	SOLDERED AT SOLDER TEMPERATURE, 245±3 °C, FOR IMMERSION DURATION, 2 s.		A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED.		<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
					
REMARK <sup>(1)</sup> TEMPERATURE RISE INCLUDED WHEN ENERGIZED. <sup>(2)</sup> THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED.				APPROVED	HS.OKAWA 06.04.12
				CHECKED	HS.OZAWA 06.04.12
				DESIGNED	KY.NAKAMURA 06.04.11
Unless otherwise specified, refer to MIL-STD-202.				DRAWN	AK.SUZUKAWA 06.04.11
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-084168-21
	SPECIFICATION SHEET		PART NO.	A2-*PA-2.54DS (71)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL620	 1/1