


PROPRIETARY INFORMATION:

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC.

REVISION

REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE, RFS. 20181, JN	12/20/10	BS

A

B
GENERAL SPECIFICATIONS:

RATING: 10A / 250V
 CABLE TYPE / SIZE: SVT, 18 AWG X 3 CONDUCTORS
 TEMPERATURE RATING: 105° C
 CONDUCTOR COLORS: BLACK / WHITE / GREEN
 CABLE JACKET COLOR: BLACK
 OVERALL LENGTH (L): 3700± 50 mm
 CABLE OUTER DIAMETER: 6.3 ± 0.1 mm
 END 'A' PLUG: IEC 320 / C14 MALE
 END 'B': IEC 320 / C13 FEMALE
 APPROVALS PLUG: UL, CSA OR cUL
 APPROVALS CABLE: UL, CSA OR cUL
 APPROVALS CONNECTOR: UL, CSA OR cUL

PACKING:

BULK PACK

NOTES:

1. CORD, PLUG AND CONNECTOR MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).



OR



DASH NO.	PART NO	REV.	DESCRIPTION	NOTES
TABULATION BLOCK				
		TOLERANCES: DECIMALS .xx +/- 0.1 .xxx +/- .005 MILLIMETERS .xx +/- 0.3 .xxx +/- .013		GlobTek, Inc. www.globtek.com 186 Veterans Dr. Northvale, NJ 07647 Tel. 201-784-1000 Fax 201.784.0111
INIT.BY: JN	DATE: 12/20/10	FSCN No.: G, CC	SIZE A	DWG TITLE: NORTH AMERICAN DETACHABLE CORDSET
DRAWN: NF	DATE: 12/20/10	SCALE: NONE	PART NO: 70114512F705(R)	REV. A
APRVD: HM	DATE: 12/20/10			SHEET 1/1

Foot Note:
Globtek Inc. will not be liable for the safety and performance of these power product if unauthorized access and repair occurs. End user should consult the applicable UL, CSA or EN Standards for proper installation instruction.

Limitation of Use:
Globtek product are not authorized for use as mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.

Contents of this document are subject to change without prior notice