

MICRO SWITCH

A DIVISION OF HONEYWELL-CONTRACTOR COMPANY
MINNEAPOLIS, MINN.

FED. MFR. CODE 91929

SWITCH-ENCLOSED

CATALOG LISTING

151ML1

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH A DIVISION OF
HONEYWELL THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH

M

151ML1

M

DRAWING
NUMBER

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

12

(M) 151ML1

REPLACES

RELEASE NO.

4 APR 58

4 APR 58

4 APR 58

4 APR 58

4 APR 58

4 APR 58

4 APR 58


4 APR 58

4 APR 58

4 APR 58

4 APR 58

4 APR 58



ROLLER LEVER MAY BE REVERSED

OPERATING POSITION

OPERATING POSITION

FREE POSITION

RELEASE POSITION

RELEASE POSITION

NOTES

- 1 - IT IS ESSENTIAL TO PREVENT ENTRANCE OF HARMFUL AGENTS THRU THE CONDUIT OPENING TO OBTAIN THE FULL BENEFIT OF THE SEALED CONSTRUCTION PROVIDED IN THIS UNIT
- 2 - SWITCH IS ASSEMBLED FOR ACTUATION IN EITHER DIRECTION
- 3 - LEVER MAY BE POSITIVELY LOCKED AT INTERVALS OF APPROX 0.4° (870 POSITIONS)
- 4 - LEVER MAY BE ADJUSTED TO ACTUATE THE SWITCH IN THE CLOCKWISE DIRECTION ONLY, THE COUNTER-CLOCKWISE DIRECTION ONLY, OR IN BOTH DIRECTIONS
- 5 - TO CONVERT SWITCH FOR ACTUATION IN EITHER CLOCKWISE OR COUNTER-CLOCKWISE DIRECTION ONLY, REMOVE THE HEAD AND SLIDE THE CAM TOWARD THE REAR OF THE HEAD SUFFICIENTLY TO DISENGAGE FROM THE FLATS ON THE SHAFT. ROTATE THE CAM 90° IN THE OPPOSITE DIRECTION OF THE ACTUATION DESIRED AND RE-ENGAGE THE CAM WITH THE FLATS ON THE SHAFT

CHARACTERISTICS

OPERATING FORCE-----3 LBS. MAX.
 FULL OVERTRAVEL FORCE-----4 LBS. MAX.
 RELEASE FORCE-----1/4 LB. MIN.
 PRETRAVEL-----③---15° MAX.
 DIFFERENTIAL TRAVEL-----④---7° MAX.
 OVERTRAVEL-----⑤---60° MIN.

SWITCH-BASIC REPLACEMENT-----IMNI

ELECTRICAL DATA (IMNI)

CONTACT ARRANGEMENT
TWO CIRCUIT DOUBLE THROW
DOUBLE BREAK

② 10A-120, 240, 480, OR 600 VAC
 1/2 HP-120 VAC, 1 HP-240 VAC
 0.8 A-115 VDC, 0.4 A-230 VDC
 PILOT DUTY 600 VAC MAX



SCALE 1/2 TO 1

DO NOT SCALE PRINT

UNLESS OTHERWISE
SPECIFIED

DIMENSIONS ARE IN INCHES

TOLERANCES ARE:

ONE PLACE (.01) ±.005
 TWO PLACE (.001) ±.001
 THREE PLACE (.000) ±.000
 ANGLES 1/2°

WEIGHT