

WEC22H -

1

2

3

4

5

FUNCTION CODE	SWITCH FUNCTION DESCRIPTION
1	NORMALLY OPEN, MOMENTARY
2	NORMALLY OPEN, MAINTAINED
3	NORMALLY CLOSED, MOMENTARY
4	NORMALLY CLOSED, MAINTAINED

HOUSING CODE	HOUSING DESCRIPTION
1	STAINLESS STEEL
S	ALUMINUM ANODIZED SILVER
K	ALUMINUM ANODIZED BLACK

BUTTON CODE	BUTTON DESCRIPTION
02	HALO ILLUMINATION STAINLESS STEEL
03	HALO ILLUMINATION ALUMINUM ANODIZED SILVER
04	HALO ILLUMINATION ALUMINUM ANODIZED BLACK

LED COLOR CODE	COLOR
A	RGB


ICON CODE	ICON
03	 POWER/STANDBY
XX	CUSTOMIZED

MECHANICAL CHARACTERISTICS:
SWITCH FUNCTION : (PER CHART)
PANEL THICKNESS : 0.5 - 4.5 mm
NUT TORQUE FORCE : MAX 10 LB-in [11.5 kgf-cm]


ENVIROMENTAL SPECIFICATIONS:
ACTUATOR INGRESS PROTECTION : IP67 FRONT PANEL
OPERATING TEMPERATURE : -40 to +185 F [-40 to +85 C]
IMPACT RESISTANCE : IK10

ELECTRICAL SPECIFICATIONS:
WORKING VALTAGE : 8~24VDC
OPEN COLLECTOR RATING : 1.5A MAX@24VDC MAX
POWER CONSUMPTION : ACTIVE : 1.5mA / SLEEP : 3.5uA
LED POWER CONSUMPTION : MAX 25mA
ELECTRICAL LIFE : 10KK CYCLES NOMINAL
ESD RESISTANCE: ±4KV
CONTACT RESISTANCE : MAX 250 mOHMS (N-MOS TYPE)

NOTE
1. ACTIVATED BY A FINGER, EVEN WITH SURGEON GLOVES.
2. SUPPLY HEX NUT AND SEALING WASHER BULK PACKED.
3. NPN OUTPUT MEANS WHEN THE SENSOR SENSES AN OBJECT, IT WILL CONNECT THE OUTPUT TO THE NEGATIVE SUPPLY. (OPEN COLLECTOR)




SUGGESTED CIRCUITRY




DWG TYPE SALES DRAWING	DRAWN C.C.	TOLERANCES: UNLESS OTHERWISE NOTED X.X ± 0.5 X.XX ± 0.1 ANGULAR ±1°	DWG TITLE WEC22H SERIES ELECTRIC CAPACITY SWITCHES						
STATUS RELEASE	REVIEW J.S.								
This document is the intellectual property of ITW Electronic Business Asia Co., Limited and may contain confidential, proprietary, privileged information protected by law. Neither this document nor any information it contains can be reproduced, transformed to any other format, or distributed, without written permission by ITW Electronic Business Asia Co., Limited. 本文作為安達德百電股份有限公司之智慧財產，非經許可不得翻印、複製、轉變成其他形式使用或散佈	APPROVED V.V.	THIRD ANGLE PROJECTION 	DWG NO. WEC22H						
	DATE 2021/06/09	REF: --							

EC22H



WIRE COLOR	DESCRIPTION
WHITE	VOLTAGE IN
YELLOW	SIGNAL
BLACK	GROUND
RED	RED LED-
GREEN	GREEN LED-
BLUE	BLUE LED-



DWG TYPE SALES DRAWING	DRAWN C.C.	TOLERANCES: UNLESS OTHERWISE NOTED X.X ± 0.5 X.XX ± 0.1 ANGULAR ±1°	DWG TITLE WEC22H SERIES ELECTRIC CAPACITY SWITCHES					
STATUS RELEASE	REVIEW J.S.		DWG NO. WEC22H					
This document is the intellectual property of ITW Electronic Business Asia Co., Limited and may contain confidential, proprietary, privileged information protected by law. Neither this document nor any information it contains can be reproduced, transformed to any other format, or distributed, without written permission by ITW Electronic Business Asia Co., Limited. 本文作為安天德百電股份有限公司之智慧財產，非經許可不得 翻取、複製、轉變成其他形式使用或散佈	APPROVED V.W.	THIRD ANGLE PROJECTION 					■ 管制文件 □ 非管制文件 Unit MM SCALE 3:2 REV 1	
	DATE 2021/06/09	REF: --						