

Pico-Clasp Discrete Wire Cable Assemblies

molex®

Pico-Clasp Discrete Wire Cable Assemblies deliver off-the-shelf (OTS) solutions with a broad offering of Molex connectors and a variety of cable lengths to facilitate both prototyping and global production


Features and Benefits

Pico-Clasp Cable Assembly offers a small 1.00mm pitch and 1.0A current rating with positive lock

Delivers space savings and prevents wire hooking

Pin-to-pin mapping from receptacle to PCB header

Provides ready-to-use, plug-and-play connections



Pico-Clasp Standard Discrete Wire Cable Assemblies



Pico-Clasp Cable Assembly

Custom assemblies for production also available

Meet design needs after prototyping is complete. Molex's extensive design and manufacturing expertise can meet the unique challenges of the most demanding applications

UL 1061 discrete wires

Ready to use in electronic appliance applications. Provide ease of design, prototyping and production

Meets 2011/65/EU RoHS Compliance

Decreases engineering time and resources

Assembled in ISO/TS16949-certified facilities

Ensures high quality. Meets current automotive industry standards

Applications

Consumer

- Fitness equipment
- Home entertainment systems
- Home appliances
- Home office
- Home security systems
- Portable electronic devices
- Gaming consoles
- Mobile devices

Commercial Vehicle

Industrial

- Process controls

Medical

- Patient monitors



Gaming Machines



Office Equipment



Industrial Automation

Pico-Clasp Discrete Wire Cable Assemblies



Specifications

REFERENCE INFORMATION

Packaging: 50 or 100 SPQ
CABLE UL File No.: UL1061
Mates With: Series 501190 and 501571
Designed In: Millimeters
RoHS: Yes
Halogen Free: No
Glow Wire Compliant: No

ELECTRICAL

Voltage (max.): 50V
Current (max.): 1.0A
Contact Resistance: 20 milliohms
Dielectric Withstanding Voltage: 250V AC
Insulation Resistance: 100 Megohms

MECHANICAL

Contact Insertion Force (max.): 4.9N
Contact Retention to Housing (min.): 4.9N
Mating Force: See 5011890000-A00, 5011890000-A01, PS-501190-001-001, PS-501571-001-001
Unmating Force: See 5011890000-A00, 5011890000-A01, PS-501190-001-001, PS-501571-001-001

PHYSICAL

Housing: See 5011890000-A00, 5011890000-A01, PS-501190-001-001, PS-501571-001-001
Contact: See 5011890000-A00, 5011890000-A01, PS-501190-001-001, PS-501571-001-001
Plating:
Contact Area — Tin
Solder Tail Area — Tin
Underplating — Tin
Operating Temperature: -40 to +85°C

Ordering Information

Series No.	Component	Type	Circuits	Length (m)
15133	Off-The-Shelf Pico-Clasp Receptacle Cable Assemblies	Single	2 to 8	50, 100, 150, 300, 450, 600

Custom Product	Description
Contact Molex	Pico-Clasp Discrete Wire Cable Assembly

www.molex.com/link/otscableassemblies.html

Molex is a registered trademark of Molex, LLC in the United States of America and may be registered in other countries; all other trademarks listed herein belong to their respective owners.