


# DX07BN24JA2R1300

## Product Details



Part Number	DX07BN24JA2R1300
Status	Active
Features	Receptacle, 24 pos., 2-row SMT, Mid-mount, Without rear shield, Center height: -0.64mm
Number of Positions	24 pos.
Rated Current	5 A max.
Rated Voltage	48 Vr.m.s.
Applicable Specifications	USB 3.2 Gen2 Type-C
Waterproof/ Non-waterproof	
Applications	Smartphones, Game machine, Drive recorder, Digital still cameras, HDD/SSD, Hub, Printer, and others
Connector Type	Receptacle
Connector Style	Right angle
PCB Mounting Method	2 row SMT horizontal
Replacement	
USB-IF Certification	Certified

<b>TID</b>	5,200,000,754
<b>Mounting Type</b>	Mid-mount
<b>Center Height</b>	-0.64 mm
<b>Recommended Board Thickness</b>	
<b>Finish of Contact in Connecting Area</b>	Gold plating over Nickel
<b>Shell</b>	Without rear shield
<b>Contact Resistance</b>	40 milliohm max. initial
<b>Dielectric Withstanding Voltage</b>	AC 100 Vr.m.s. (1 minute)
<b>Insulation Resistance</b>	100 megaohm min.
<b>Operating Temperature Range</b>	-40 deg. C to +85 deg. C
<b>Mating Cycles</b>	10,000 times
<b>Packaging Type</b>	Embossed tape packaging
<b>Quantity in The Standard Packaging</b>	1,300 pcs./reel
<b>Documents</b>	<a href="#">Catalog </a> <a href="#">Drawings </a> <a href="#">Drawings </a> <a href="#">3D Models &gt;</a> <a href="#">PDF Download </a>
<b>Stock Search</b>	<a href="#">Stock Search &gt;</a>
<b>RoHS compliant</b>	10 substances (2011/65/EU, (EU)2015/863)
<b>REACH compliant</b>	223 substances (17/01/2022)

**Notice**

1. The values specified in this web site are only for reference. The products and their specifications are subject to change without notice. Contact our sales staff for further information before considering or ordering any of our products.  
For purchase, a product specification must be agreed upon.
2. Users are requested to provide protection circuits and redundancy circuits to ensure safety of the equipment, and sufficiently review the suitability of JAE's products to the equipment.
3. The products presented in this web site are designed for the uses recommended below.

We strongly suggest you contact our sales staff when considering use of any of the products in any other way than the recommended applications or for a specific use that requires an extremely high reliability.

(1) Applications that require consultation:

\*Please contact us if you are considering use involving a quality assurance program that you specify or that is peculiar to the industry, such as:

Automotive electrical components, train control, telecommunications devices (mainline), traffic light control, electric power, combustion control, fire prevention or security systems, disaster evention equipment, etc.

\*We may separately give you our support with a quality assurance program that you specify, when you think of a use such as :

Aviation or space equipment, submarine repeaters, nuclear power control systems, medical equipment for life support, etc.

(2) Recommended applications include:

\*Computers, office appliances, telecommunications devices

(terminals, mobile units), measuring equipment, audiovisual equipment, home electric appliances, factory automation equipment, etc