


RESISTANCE VS TEMPERATURE CHARACTERISTICS:

Temp(°C)	R min (KΩ)	R nom (KΩ)	R max (KΩ)	Temp(°C)	R min (KΩ)	R nom (KΩ)	R max (KΩ)
-40	291.2	304.4	318.1	50	3.49	3.561	3.634
-35	213.6	222.6	231.9	55	2.879	2.944	3.01
-30	158.3	164.4	170.8	60	2.388	2.446	2.505
-25	118.4	122.6	127	65	1.989	2.041	2.095
-20	89.39	92.32	95.34	70	1.664	1.711	1.759
-15	68.17	70.21	72.31	75	1.399	1.44	1.483
-10	52.38	53.81	55.27	80	1.18	1.217	1.256
-5	40.53	41.53	42.55	85	1.001	1.034	1.069
0	31.58	32.27	32.98	90	0.853	0.882	0.913
5	24.72	25.2	25.69	95	0.729	0.756	0.783
10	19.48	19.82	20.15	100	0.625	0.649	0.674
15	15.46	15.68	15.91	105	0.539	0.56	0.582
20	12.33	12.49	12.64	110	0.465	0.484	0.504
25	9.9	10	10.1	115	0.403	0.42	0.438
30	7.955	8.053	8.151	120	0.351	0.366	0.382
35	6.427	6.52	6.613	125	0.306	0.32	0.334
40	5.218	5.304	5.392	130	0.261	0.274	0.286
45	4.257	4.337	4.417	135	0.216	0.228	0.238

NOTES:

1. RESISTANCE @ 25°C : 10KΩ±1%.
2. BETA VALUE (0/50°C) : 3892K±1%
3. OPERATING TEMPERATURE RANGE : -40°C TO +135°C.
4. DISSIPATION FACTOR : 1.5mW/°C
5. THERMAL TIME CONSTANT : LESS THAN 3SECONDS IN WATER
- 6.INSULATION RESISTANCE : 10MΩ AT 100 VDC



FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION														
	DIMENSION UNITS		SCALE		CURRENT REV DESC:					molex					
	mm		NTS												
	GENERAL TOLERANCES (UNLESS SPECIFIED)				EC NO: 657230 DRWN: RAVIKM CHK'D: RBBHASKAR APPR: RBBHASKAR INITIAL REVISION: DRWN: RAVIKM APPR: RBBHASKAR					NTC EPOXY - 3892 100MM 10K1%					
	ANGULAR TOL ± °														
	4 PLACES		±												
	3 PLACES		±												
	2 PLACES		±												
	1 PLACE		±												
	0 PLACES		±												
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				THIRD ANGLE PROJECTION		DRAWING		SERIES		MATERIAL NUMBER		CUSTOMER		SHEET NUMBER	
						A3-SIZE		215272		2152723607		OTS		1 OF 1	