






Material and Finish

Shell: steel, nickel plated

Insulator: PBT with glass-fiber reinforcement, UL 94V-0 rated, color-black

Contact Material:

Plug: Brass

Contact Plating:

Standard:
Gold flash on mating end, tin on termination end, with entire contact nickel underplated

-15 Option:
15u" gold on mating end, tin on termination end, with entire contact nickel underplated

-30 Option:
30u" gold on mating end, tin on termination end, with entire contact nickel underplated

Electrical Specifications

Rated Current: 2A

Rated Voltage: 30V RMS

Withstanding Voltage:
500V (rms) AC for 1 minute

Insulation Resistance:
more than 1000 Megohm at 500V DC

Contact Resistance:
13 milliohm max.

Dielectric Strength:
1000V for 1 minute

Operating Temperature:
-55°C to +105°C


Part Number	Contact Area Plating Finish
K85X-AA-15P	Gold Flash (standard)
K85X-AA-15P-15	15u" Gold (15 option)
K85X-AA-15P-30	30u" Gold (30 option)

RoHS COMPLIANT



Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	3/24/06	New Drawing	H. MA	Furumasu	H. MA	3/24/06
A2	1/8/08	ECO# 07-052	WILL H.	H. MA		
A3	12/31/17	ECO #17-030	J. Elbanna	C. Furumasu		



K85X-AA-15P

Vertical Soldercup Mount D-Sub,

15 Pin Male, RoHS Compliant

