



NOTE:

MATERIAL

HOUSING:

PBT UL94V-0, BLACK

CONTACT:

BRASS

NUT:

BRASS

O-RING:

EPDM

FINISH

CONTACT:

GOLD PLATED

OVER 50 μ " NICKEL

NICKEL PLATED

NUT:

1.5A

ELECTRICAL

30V

RATED CURRENT:

100 M Ω hms MIN.

RATED VOLTAGE:

10 m Ω hms MAX.

INSULATION RESISTANCE:

IP67

CONTACT RESISTANCE:

WATER PROOF:

ENVIRONMENT

OPERATION TEMPERATURE:

-40°C TO +85°C

MAX WIRE AWG:

24

858-012-103RLUY

3 = BRASS/NICKEL NUT
S = STAINLESS STEEL NUT1 = GOLD FLASH
4 = 10 μ " GOLD

RoHS COMPLIANT

UNITS = INCHES [MM]

DO NOT SCALE FROM DRAWING



THESE DRAWINGS AND SPECIFICATIONS ARE
THE PROPERTY OF NorComp AND SHALL NOT
BE REPRODUCED, COPIED OR USED AS THE
BASIS FOR THE MANUFACTURE OR SALE OF
APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:
M. SIGMONDATE:
03-08-16

NorComp

SCALE:
NTSSHEET
1 OF
1 1REV
5

DWG NO.

858-012-103RLUY