

| APPLICABLE STANDARD | | SPECIFICATIONS | | | |
|---------------------|--------------------------------|--------------------------------|------------------------------|---------------------------------|--|
| RATING | OPERATING TEMPERATURE RANGE | -55 °C TO 85 °C ⁽¹⁾ | STORAGE TEMPERATURE RANGE | -10 °C TO +60 °C ⁽²⁾ | |
| | OPERATING HUMIDITY RANGE | 40 % TO 80 % | STORAGE HUMIDITY RANGE | 40 % TO 70 % ⁽²⁾ | |
| | VOLTAGE | 200 V AC | APPLICABLE CABLE | AWG #26 TO #36 | |
| | CURRENT | 2 A | INSULATION | — | |

| | COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE |
|--|-------|---------------------------|-------------|-----------------|------------------|
| | | | | | |
| REMARK | | | | | |
| (1) TEMPERATURE RISE INCLUDED WHEN ENERGIZED. | | | APPROVED | HS. OKAWA | 15. 06. 08 |
| (2) THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED. | | | CHECKED | HT. YAMAGUCHI | 15. 06. 08 |
| Unless otherwise specified, refer to MIL-STD-1344. | | | DESIGNED | MT. ITANO | 15. 06. 08 |
| | | | DRAWN | MT. ITANO | 15. 06. 08 |
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test | | | DRAWING NO. | | ELC-021405-00-00 |
| | | SPECIFICATION SHEET | PART NO. | A4B-5S-2C | |
| | | HIROSE ELECTRIC CO., LTD. | CODE NO. | CL622-0304-1-00 | 1/1 |