

**Sales Outline Drawing**Revision **A****Specifications:**

|  |                                   |
|--|-----------------------------------|
| Oscillation Frequency (Hz)                         | 2731                              |
| Operating Voltage (Vp-p)                           | 1.25 ~ 2.5                        |
| Rated Voltage (Vp-p)                               | 1.5                               |
| Current Consumption Max. (mA)                      | 85 at Rated Voltage               |
| Sound Pressure Level (dB/min)                      | 72 at 10cm at Rated Voltage       |
| Coil Resistance ( $\Omega$ )                       | $5.5 \pm 1$                       |
| Operating Temperature ( $^{\circ}\text{C}$ )       | -20 ~ +70                         |
| Storage Temperature ( $^{\circ}\text{C}$ )         | -30 ~ +80                         |
| Lead Pin   | Tin Plated Brass                  |
| Housing  | PPO plastic resin (Color : Black) |
| Weight (Grams)                                     | .8                                |
| Condition by wave soldering ( $^{\circ}\text{C}$ ) | $260 \pm 5$ / within 5 sec        |
| Condition by hand soldering ( $^{\circ}\text{C}$ ) | $350 \pm 20$ / within 5 sec       |
| Options  | For other options contact factory |

**Dimensions:** (units: mm)**PS: Vp-p = 1/2duty, square wave****ROHS Compliant**