





PART NUMBER	DESCRIPTION
B-0875CC1125-0325XC	COVER
B-0875SB1125-0325XF	FRAME



RoHS Compliant		DIMENSIONS ARE IN INCHES [MILLIMETERS]		
THIRD ANGLE PROJECTION		FRACTIONAL \pm		
DO NOT SCALE DRAWING		ANGULAR: MACH \pm 3 Degrees		
PROPRIETARY AND CONFIDENTIAL		TWO PLACE DECIMAL \pm .015 (.381)		
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ORBEL CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ORBEL CORPORATION IS PROHIBITED.		THREE PLACE DECIMAL \pm .010 (.254)		
MATERIAL: .010" [.254] NICKEL SILVER, 1/2 HARD		MATERIAL:		
FINISH:		FINISH:		
		WEIGHT: 0.077oz. [2.192g]	COMMENTS:	


ORBEL
ENGINEERED SOLUTIONS

SIZE DWG NO. A B-0875CC1125-0325XC REV. 01
SCALE: 2:1 CAGE CODE: 57DU2 SHEET 1 OF 1

HOW TO ORDER BOARD LEVEL SHIELDING


The chart below is an easy-to-use reference on how Orbel BLS part numbers are created and used to order standard and custom board level shielding. Custom configurations that fall outside of our standard shield styles are also available.

Sample Part Number (Snap-Shield Bullseye™): B-0750TB1125-0250XF - TPS




STANDARD FEATURES


PIN OPTIONS




Alignment Pin




Through-Hole Pin



Through-Hole Pin with Standoff




Castellation Edge




Straight Edge, No Pin


CORNER OPTIONS



Tight Corner




Louvered Corner




Welded Corner

ADDITIONAL OPTIONS



Trace Notch



Pick Target



Ventilation Holes



Logo or Part Number Marking

PERFORMANCE Specs

Material Options

- Nickel Silver
- TPS: Tin-Plated Steel
- TPB: Tin-Plated Brass
- TPC: Tin-Plated Copper

Co-Planarity

- Smaller Shields: 0.004"
- Larger Shields: 0.008"

Material Thicknesses

- 0.010" (Standard)
- 0.008"
- 0.012"
- 0.015"

RoHS-Compliant

- Yes

Shielding Effectiveness

- Up to 60dB

Other material options include beryllium copper, phosphorus bronze, and stainless steel. Additional plating finishes available upon request.

All technical data presented herein is accurate to the best of our knowledge based on Orbel's most up-to-date testing information and material specs. This information is not presented as a warranty or guarantee and is not intended to be all-inclusive as to conditions of use.