DATE	REV	ECN	APP'D. BY
10-29-21	A0	11878	ABD
2-7-22	A1	11929	JME



NOTES:

1) MFi CERTIFIED
2) EACH CABLE ASSEMBLY TO BE INDIVIDUALLY BAGGED.
3) CABLE CONSTRUCTION PVC
   - 3.7MM OD
   - WHITE JACKET
4) CONNECTOR P1: USB A MALE 2.0 WHITE INSULATOR,
   - NICKEL PLATED TIN SHELL
   - WHITE PVC EXTERIOR MOLDING
5) CONNECTOR P2: i5 C89
   - NICKEL PLATED TIN SHELL
   - WHITE PVC EXTERIOR MOLDING
6) ALL CABLES TESTED FOR CONTINUITY & SHORTS
   - CONTACT RESISTANCE 3 OHM MAX.
   - INSULATION RESISTANCE 10M OHM

P/N STRUCTURE:

SC-2AZWxxxF

- F = FEET
- LENGTH: 100FT=100, 10FT=010, 1FT=001
- W = WHITE
- Z = LIGHTNING CABLE
- A = USB TYPE A
- 2 = USB 2.0
- CABLE ASSEMBLY FAMILY

O/A Length Tolerance:

Metric
915mm ±20mm
1830mm ±30mm

Imperial
3ft ±0.5in
6ft ±0.75in

Pin Assignment

USB AM		C89	
1	Red	1	VBUS
2	White	2	D−
3	Green	3	D+
4	Drain	5	GND1
SHELL	Braid	SHELL	

PART NUMBERS REFERENCE TABLE	
LENGTH	PART NUMBER
3 FT	SC-2AZW003F
6 FT	SC-2AZW006F

RoHS

THIRD ANGLE PROJECTION

DO NOT SCALE DRAWING
DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE
DIMENSIONS: METRIC
UNLESS OTHERWISE SPECIFIED TOLERANCES ARE ±0.13 ANGLES ARE ± 1°
SHEET NO. 1 OF 1

bel
206 Van Vorst Street
Jersey City, NJ 07302
+1 201 432 0463
http://www.belfuse.com

TITLE: USB 2.0 to i5 C89 Lightning Cable White

THIS DRAWING AND THE SUBJECT MATTER SHOWN THEREON ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF BEL FUSE, INC. AND SHALL NOT BE REPRODUCED, COPIED, OR USED IN ANY MANNER WITHOUT PRIOR WRITTEN CONSENT OF BEL FUSE, INC.

DRN BY:	JMM	DATE	10-27-21
APPD BY:	ADB	DATE	10-29-21
DWG NO.	CT999270	REV.	A1

AutoCAD