

Applicable standard		Specifications					
Rating	Operating Temperature range	-40 °C to +105°C (Note1)	Storage Temperature range	-10 °C to +60°C (Note3)			
	Operating Humidity range	20% to 80% (Note2)	Storage Humidity range	40% to 70% (Note3)			
	Applicable Connector	DF62W-4EP-2.2C(##)		Voltage	AC/DC 250V		
	Applicable contact	DF62W-2226SC*		Current	AWG 22 : 3A AWG 24 : 2A AWG 26 : 1A		
Construction							
General examination	Visually and by measuring instrument.		According to drawing.		X X		
Marking	Confirmed visually.				X X		
Electric characteristics 							
Insulation resistance	500 V DC.		1000 MΩ MIN.		X —		
Voltage proof	650 V AC for 1 min.		No flashover or breakdown.		X —		
Mechanical characteristics 							
Mechanical operation	30 times insertion and extraction.		No damage, crack or looseness of parts.		X —		
Vibration	Frequency 10 to 55 Hz, single amplitude 0.75 mm, at 10 cycles for 3 direction.		No damage, crack or looseness of parts.		X —		
Shock	490 m/s ² duration of pulse 11 ms at 3 times each for 3 both axial directions.		No damage, crack or looseness of parts.		X —		
Environmental characteristics 							
Damp heat (Steady state)	Exposed at 40 ± 2°C , 90 to 95 %, 96 h. (After leaving the room temperature for 1~2h.)		①Insulation resistance: 1000 MΩ Min. ②No damage, crack or looseness of parts.		X —		
Rapid change of temperature	Temperature -55°C → +85°C Time 30min → 30min Under 5 cycles. (The transferring time of the tank is 2~3 min) (After leaving the room temperature for 1~2h.)		①Insulation resistance: 1000 MΩ Min. ②No damage, crack or looseness of parts.		X —		
Note 1: Include the temperature rising by current. Note 2: No condensing Note 3: Apply to the condition of long term storage for unused products before PCB on board. After PCB on board, operating temperature and humidity range is applied for interim strage during transportation.							
Count	Description of revisions		Designed	Checked	Date		
 3	DIS-H-008782		KT. ISHII	HK. UMEHARA	14. 05. 23		
Remarks				Approved	KI. AKIYAMA		
				Checked	HK. UMEHARA		
				Designed	KT. ISHII		
Unless otherwise specified, refer to IEC 60512.				Drawn	KT. ISHII		
Note QT:Qualification Test AT:Assurance Test X:Applicable Test				Drawing No. ELC4-353725-00			
	Specification sheet		Part No.	DF62W-4S-2. 2C			
	HIROSE ELECTRIC CO., LTD.		Code No.	CL544-1006-8-00	 1/1		