



Selector switch, 22 mm, round, metal, shiny, white, Rotary knob, 4 switch positions I-II-III-IV, latching, Actuating angle 4x90°, 3h/6h/9h/12h

|                                                    |                                    |
|----------------------------------------------------|------------------------------------|
| product brand name                                 | SIRIUS ACT                         |
| product designation                                | Selector switches                  |
| design of the product                              | Actuating/signaling element        |
| product type designation                           | 3SU1                               |
| product line                                       | Metal, shiny, 22 mm                |
| <b>Enclosure</b>                                   |                                    |
| number of command points                           | 1                                  |
| <b>Actuator</b>                                    |                                    |
| design of the actuating element                    | Rotary knob                        |
| principle of operation of the actuating element    | Latching, 4x90° (3/6/9/12 o'clock) |
| product extension optional                         |                                    |
| • light source                                     | No                                 |
| • contact module                                   | Yes                                |
| color of the actuating element                     | white                              |
| material of the actuating element                  | plastic                            |
| shape of the actuating element                     | Button                             |
| outer diameter of the actuating element            | 29.5 mm                            |
| number of switching positions                      | 4                                  |
| actuating angle                                    |                                    |
| • clockwise                                        | 360°                               |
| • anticlockwise                                    | 360°                               |
| <b>Front ring</b>                                  |                                    |
| product component front ring                       | Yes                                |
| design of the front ring                           | standard                           |
| material of the front ring                         | Metal, high gloss                  |
| color of the front ring                            | silver                             |
| <b>General technical data</b>                      |                                    |
| protection class IP                                | IP66, IP67, IP69(IP69K)            |
| degree of protection NEMA rating                   | 1, 2, 3, 3R, 4, 4X, 12, 13         |
| shock resistance                                   |                                    |
| • according to IEC 60068-2-27                      | sinusoidal half-wave 15g / 11 ms   |
| vibration resistance                               |                                    |
| • according to IEC 60068-2-6                       | 10 ... 500 Hz: 5g                  |
| operating frequency maximum                        | 1 800 1/h                          |
| mechanical service life (switching cycles) typical | 300 000                            |
| reference code according to IEC 81346-2            | S                                  |
| Substance Prohibitance (Date)                      | 10/01/2014                         |
| <b>Ambient conditions</b>                          |                                    |
| ambient temperature                                |                                    |

- during operation
- during storage

-25 ... +70 °C

-40 ... +80 °C

environmental category during operation according to IEC 60721

3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%)

#### Installation/ mounting/ dimensions

|                                             |         |
|---------------------------------------------|---------|
| height                                      | 29.5 mm |
| width                                       | 29.5 mm |
| shape of the installation opening           | round   |
| mounting diameter                           | 22.3 mm |
| positive tolerance of installation diameter | 0.4 mm  |
| mounting height                             | 28.8 mm |
| installation width                          | 29.5 mm |
| installation depth                          | 29.4 mm |

#### Certificates/ approvals

General Product Approval

Declaration of Conformity



[Confirmation](#)



EG-Konf.

Test Certificates

Marine / Shipping

[Type Test Certificates/Test Report](#)



ABS



LRS



PRS



RINA



RMRS

other

[Environmental Confirmations](#)

[Confirmation](#)

#### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1050-2AS60-0AA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1050-2AS60-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1050-2AS60-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SU1050-2AS60-0AA0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1050-2AS60-0AA0&lang=en)

last modified:

1/26/2022