



PCB LAYOUT
(Top View)

RoHS compliant
Unit:mm

Scale	Free								
TOLERANCE									
.XX	±0.20								
.XXX	±0.13								
.XXXX	±0.05								
DIM	TOL								
Angle	+0°30'	Id.	Drawn	Modification	Date	Name			
			①		04.08.2016	Winnie			

Date	Name	Date	Name
04.08.2016	Winnie	04.08.2016	Winnie
Approved	04.08.2016	Winnie	

ASSMANN
components

Customer-No.	
ASSMANN WSW-No.	A-2004-2-4-LPS-N-R
Drawing-No.	ASS 7323 CO
Replace	rev00
	SHEET

Specification:

1. Electrical Char
Insulation Resistance: 500MΩ min. 500V DC for 1 minute
Contact Resistance: 30mΩ max.
Rating Current: 1.5A max.
Rating Voltage: 150V AC
Dielectric Voltage: 1000 Vrms at 1MA 60 sec. min.

2. Physical Char

Housing: PBT Glass filled (UL 94V-0) Color: Black
Soldering Temperature: 235°C for 5 sec.
Spring Wire: 0.45mm Dia Phosphor Bronze
6u" Gold plating over Nickel
Temperature Range: -40°C to +85°C
Durability: 750 mating cycles min.

3. Packing: Tray

1	2	3	4	5	6	7	A
1	2	3	4	5	6	7	H