

| APPLICABLE STANDARD | | SPECIFICATIONS | | | | |
|---|---|---|---------------------------|---|-----------------|-------|
| RATING | FREQUENCY RANGE | DC ~ 50 GHz | STORAGE TEMPERATURE RANGE | -55°C ~ + 125°C (No Load) (※1) | | |
| | POWER | 1 W CW (AT 65°C) | CHARACTERISTIC IMPEDANCE | 50 Ω | | |
| | OPERATING TEMPERATURE RANGE | -10 °C TO +65 °C | APPLICABLE CABLE | --- | | |
| | OPERATING RELATIVE HUMIDITY | ~ 90 % | USED CONNECTOR | H2.4-P, H2.4-J | | |
| CONSTRUCTION | | | | | | |
| GENERAL EXAMINATION | VISUALLY AND BY MEASURING INSTRUMENT. | | ACCORDING TO DRAWING. | | X X | |
| MARKING | CONFIRMED VISUALLY. | | | | X X | |
| ELECTRIC CHARACTERISTICS | | | | | | |
| V.S.W.R | MUST BE UNDER THE STD.VALUE AT FREQUENCY DC TO 50 GHz | | | 1.3 MAX (DC ~ 12 GHz) | X X | |
| | | | | 1.4 MAX (12 ~ 50GHz) | | |
| INSERTION LOSS | MUST BE UNDER THE STD.VALUE AT FREQUENCY DC TO 50 GHz | | | 4.6dB ~5.8 dB (DC ~18GHz) | X X | |
| | | | | 4.6dB ~6 dB (18 ~26.5GHz) | | |
| | | | | 4.6dB ~6.8 dB (26.5 ~50GHz) | | |
| INSULATION RESISTANCE | MUST BE OVER STANDARD VALUE AT DC V. | | | MINIMUM OF MΩ | — — | |
| VOLTAGE PROOF | V AC FOR 1 min. CURRENT LEAKAGE 2mA MAX. | | | NO FLASHOVER OR BREAKDOWN. | — — | |
| RESISTANCE VALUE | MEASURE THE RESISTANCE VALUE AT DC V. | | | MAX | — — | |
| MECHANICAL CHARACTERISTICS | | | | | | |
| MECHANICAL OPERATION | 500 TIMES INSERTIONS AND EXTRACTIONS. | | | ① ELECTRICAL CHARACTERISTIC SHALL BE MET. ② NO DAMAGE, CRACK, AND LOOSENESS, OF PARTS. | X — | |
| VIBRATION | FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm OR 1 oct/min AT 10 CYCLES FOR 3 DIRECTIONS. | | | ① ELECTRICAL CHARACTERISTIC SHALL BE MET. ② NO DAMAGE, CRACK, AND LOOSENESS, OF PARTS. | X — | |
| SHOCK | 490 m/s ² AT 18 TIMES FOR 3 DIRECTIONS. | | | ① ELECTRICAL CHARACTERISTIC SHALL BE MET. ② NO DAMAGE, CRACK, AND LOOSENESS, OF PARTS. | X — | |
| ENVIRONMENTAL CHARACTERISTICS | | | | | | |
| RAPID CHANGE OF TEMPERATURE | TEMPERATURE -55 → 15~25 → 125 → 15~25 °C TIME 30 → 2~3 → 30 → 2~3 min UNDER 100 CYCLES. | | | ① ELECTRICAL CHARACTERISTIC SHALL BE MET. ② NO HEAVY CORROSION. | X — | |
| DAMP HEAT (STEADY STATE) | EXPOSED AT 40 °C, 90% TO 95% TOTAL 96 h. | | | ① ELECTRICAL CHARACTERISTIC SHALL BE MET. ② NO HEAVY CORROSION. | X — | |
| DRY HEAT | EXPOSED AT 125 °C TOTAL 48 h. | | | ① ELECTRICAL CHARACTERISTIC SHALL BE MET. ② NO HEAVY CORROSION. | X — | |
| COLD | EXPOSED AT -55 °C TOTAL 48 h. | | | ① ELECTRICAL CHARACTERISTIC SHALL BE MET. ② NO HEAVY CORROSION. | X — | |
| CORROSION SALT MIST | EXPOSED IN 5±1 % SALT WATER, AT 35±2°C SPRAY FOR 48 HOURS. | | | 1.3 MAX (DC ~ 12 GHz) 1.4 MAX (12 ~ 50GHz) | X — | |
| REMARKS | | RoHS COMPLIANT High frequency performance is only measured and the data is not attached. (※1) The storage temperature range means the one of the product itself without packaging. Unless otherwise specified, refer to IEC 60512. | | | | |
| Note QT:Qualification Test AT:Assurance Test X:Applicable Test | | DRAWING NO. | | ELC-384092-00-00 | | |
|  | | SPECIFICATION SHEET | | PART NO. | H2.4-AT(5)-PJ | |
| | | HIROSE ELECTRIC CO., LTD. | | CODE NO. | CL354-0312-0-00 | △ 1/1 |