Sep.1.2022 Copyright 2022 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C
	OPERATING&STORAGE HUMIDTY RANGE	85%MAX	APPLICABLE CABLE	2 CABLE DIAMETER : φ7.3～9.3
	VOLTAGE		CURRENT	

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X

	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
2	1	DIS-E-00003216	KN. ICHIKAWA	TU. TANIGUCHI	20201019

REMARK

THIS PRODUCT SHALL BE MATED WITH DH40-37S OR DH3＊B-37S, IT APPLIES TO DH40-37S OR DH3＊B-37S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS.

Unless otherwise specified, refer to IEC 60512.

APPROVED	KN. ICHIKAWA	20100705
CHECKED	KN. ICHIKAWA	20100705
DESIGNED	TU. TANIGUCHI	20100705
DRAWN	TU. TANIGUCHI	20100705

Note QT:Qualification Test AT:Assurance Test X:Applicable Test

DRAWING NO. ELC-126592-00-00

HRS	SPECIFICATION SHEET	PART NO.	DH-37-CV2B	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL244-0015-9-00	2 1/1

FORM HD0011-2-1