

TPS62122EVM

This user's guide describes the characteristics, operation, and use of the TPS62122 evaluation module (EVM). The TPS62122EVM-586 is a fully assembled and tested circuit for evaluating the performance of the [TPS62122](#) high-input voltage step-down converter. This document includes schematic diagrams, a printed circuit board (PCB) layout, bill of materials, and test data. Throughout this document, the abbreviation *EVM* and the term *evaluation module* are synonymous with the TPS62122EVM-586 unless otherwise noted.

Contents

1	Introduction	2
1.1	Features	2
1.2	Applications	2
2	TPS62122EVM Schematic	2
3	Connector and Test Point Descriptions	3
3.1	Enable Jumpers/Switches (RefDes) TPS62122	3
4	Test Configuration	4
4.1	Hardware Setup	4
4.2	Procedure	5
5	TPS62122EVM Test Data	5
5.1	Efficiency	5
5.2	Start-Up	6
5.3	Load Transient Response	7
5.4	Typical Operation, 60 mA	7
5.5	Typical Operation, 10 mA	8
5.6	Current Limit Operation	8
6	TPS62122EVM Assembly Drawings and Layout	9
7	Bill of Materials	12

List of Figures

1	TPS62122EVM Schematic	2
2	Hardware Board Connection	4
3	EFFICIENCY vs INPUT VOLTAGE V_{IN} ($V_{OUT} = 3.0V$)	5
4	TPS62122EVM Efficiency versus Load Current	5
5	TPS62122EVM Startup into 300- Ω Load($V_{IN} = 8.0$ V, $V_{OUT} = 3.0$ V)	6
6	TPS62122EVM Start-Up from a High-Impedance Source($V_{IN} = 12.0$ V, $V_{OUT} = 3.0$ V)	6
7	TPS62122 Load Transient Response($V_{IN} = 8.0$ V, $V_{OUT} = 1.8$ V)	7
8	TPS62122EVM Output Ripple, 60-mA Load($V_{IN} = 8.0$ V, $V_{OUT} = 3.0$ V)	7
9	TPS62122EVM Output Ripple, 10-mA Load($V_{IN} = 8.0$ V, $V_{OUT} = 3.0$ V)	8
10	Current Limit Operation	8
11	TPS62122EVM Component Placement (Top View)	9
12	TPS62122EVM Top-Side Copper (Top View)	10
13	TPS62122EVM Bottom-Side Copper (Bottom View)	11

1 Introduction

The TPS62122 is a high-efficiency, synchronous step-down, dc-dc converter optimized for low-power applications. The wide operating input voltage range of 2 V to 15 V supports energy harvesting and battery-powered as well 9-V or 12-V line-powered applications.

The TPS62122EVM-586 is a fully assembled and tested platform for evaluating the operation and performance of the TPS62122 converter. The TPS62122EVM-586 has an input voltage range from 2.0 V up to 15 V, and the output voltage is adjustable with an external feedback divider network in the range of 1.2 V to 5.5 V. The maximum output current of the EVM circuit is 75 mA.

1.1 *Features*

- High input voltage range: 2.0 V up to 15 V
- Adjustable output voltage: 1.2 V up to 5.5 V
- Up to 75-mA output current
- Up to 800-kHz switching frequency

1.2 *Applications*

- Ultralow-power microcontroller supply
- Energy harvesting
- Industrial measurement

2 TPS62122EVM Schematic

Figure 1 illustrates the TPS62122EVM-586 schematic.




Table 1 for specific values.

3 Connector and Test Point Descriptions

3.1 Enable Jumpers/Switches (RefDes) TPS62122

3.1.1 J1 VIN

This header is the positive connection to the input power supply. The power supply must be connected between J1 and J3 (GND). The leads to the input supply should be twisted and kept as short as possible. The input voltage must be between 2.0 V and 15.0 V.

3.1.2 J2 S+/S-

J2 S+/S- are the sense connection for the input of the converter. Connect a voltmeter, sense connection of a power supply, or oscilloscope to this header.

3.1.3 J3 GND

This header is the return connection to the input power supply. Connect the power supply between J3 and J11 (VIN). The leads to the input supply should be twisted and kept as short as possible. The input voltage must be between 2.0 V and 15.0 V.

3.1.4 J4 VOUT

This header is the positive output of the step-down converter. The output voltage of the TPS62122 is adjustable, with the feedback resistors R1 and R2. On the EVM, the output voltage can be adjusted in the range of 1.2 V to 5.5 V.

Note: A feed-forward capacitor is required. Refer to the [TPS62122 data sheet \(SLVSAD5\)](#) for detailed information.

3.1.5 J5 S+/S-

J5 S+/S- are the sense connection for the output of the converter. Connect a voltmeter, sense connection of an electronic load, or oscilloscope to this header.

3.1.6 J6 GND

J6 is the return connection of the converter. A load can be connected between J4 and J6 (VOUT). The converter is able to support a load current of up to 75 mA.

3.1.7 JP1 EN

This jumper enables/disables the TPS62122 on the EVM. The shorting jumper JP1 between the center pin and ON turns on the unit. Shorting the jumper between the center pin and OFF turns the unit off.

3.1.8 J7 VOUT (SMA)

The J7 SMA connector is connected to the output voltage of the TPS62122. The noise spectrum of the output voltage can be easily analyzed with a spectrum analyzer.

By default, J7 is not assembled on the EVM.

4 Test Configuration

4.1 Hardware Setup

Figure 2 illustrates a typical hardware test configuration.




Figure 2. Hardware Board Connection

4.2 Procedure

Follow these procedures when configuring the EVM for testing.

CAUTION

Many of the components on the TPS62122EVM-586 are susceptible to damage by electrostatic discharge (ESD). Customers are advised to observe proper ESD handling precautions when unpacking and handling the EVM, including the use of a grounded wrist strap, bootstraps, or mats at an approved ESD workstation. An electrostatic smock and safety glasses should also be worn.

1. Work at an ESD workstation. Make sure that any wrist straps, bootstraps, or mats are connected and reference the user to earth ground before power is applied to the EVM. Electrostatic smock and safety glasses should also be worn.
2. Connect a dc power supply between J1 and J3 on the TPS62122EVM. Note that the input voltage should range from 2.0 V to 15 V. Keep the wires from the input power supply to EVM as short as possible and twisted.
3. Connect a dc voltmeter or oscilloscope to the output sense connection (J5) of the EVM.
4. A load of up to 75 mA can be connected between J4 and J6 on the TPS62122EVM.
5. To enable the converter, connect the shorting bar on JP1 between EN and ON on the TPS62122EVM.

5 TPS62122EVM Test Data

Figure 4 through Figure 10 present typical performance graphs for the TPS62122EVM. Actual performance data can be affected by measurement techniques and environmental variables; therefore, these curves are presented for reference and may differ from actual results obtained by some users.

5.1 Efficiency

Figure 4 shows the typical efficiency performance for the TPS62122EVM.

**Figure 3. EFFICIENCY vs
INPUT VOLTAGE V_{IN} ($V_{OUT} = 3.0V$)**




Figure 4. TPS62122EVM Efficiency versus Load Current

5.2 Start-Up

Figure 5 and Figure 6 show the typical start-up performance for different TPS62122EVM boards.




Figure 5. TPS62122EVM Startup into 300- Ω Load
($V_{IN} = 8.0$ V, $V_{OUT} = 3.0$ V)




Figure 6. TPS62122EVM Start-Up from a High-Impedance Source
($V_{IN} = 12.0$ V, $V_{OUT} = 3.0$ V)

5.3 Load Transient Response

Figure 7 illustrates the load transient response for the TPS62122.




Figure 7. TPS62122 Load Transient Response
 $(V_{IN} = 8.0$ V, $V_{OUT} = 1.8$ V)

5.4 Typical Operation, 60 mA

Figure 8 illustrates the typical output voltage ripple for the TPS62122 with a 60-mA load.




Figure 8. TPS62122EVM Output Ripple, 60-mA Load
 $(V_{IN} = 8.0$ V, $V_{OUT} = 3.0$ V)

5.5 Typical Operation, 10 mA

Figure 9 illustrates the typical output voltage ripple for the TPS62122 with a 10-mA load.




Figure 9. TPS62122EVM Output Ripple, 10-mA Load
($V_{IN} = 8.0$ V, $V_{OUT} = 3.0$ V)

5.6 Current Limit Operation

Figure 10 shows the current limit operation of the TPS62122.




Figure 10. Current Limit Operation

6 TPS62122EVM Assembly Drawings and Layout

Figure 11 through Figure 13 show the design of the show the design of the TPS62122EVM-586 printed circuit board. The EVM has been designed using a four-layer, 1-ounce copper-clad PCB.

NOTE: Board layouts are not to scale. These figures are intended to show how the board is laid out; they are not intended to be used for manufacturing TPS62122EVM-586 PCBs.




Figure 11. TPS62122EVM Component Placement (Top View)




Figure 12. TPS62122EVM Top-Side Copper (Top View)




Figure 13. TPS62122EVM Bottom-Side Copper (Bottom View)

7 Bill of Materials

[Table 1](#) lists the bill of materials for the TPS62122EVM.

Table 1. TPS62122EVM-586 Bill of Materials

Count	RefDes	Value	Description	Size	Part Number	MFR
1	C1	4.7 μ F	Capacitor, Ceramic, 25 V, X5R, 20%	0805	GRM21BR61E475MA12L	muRata
0	C2	Open	Capacitor, Polymer Type, 20 V, $\pm 20\%$	3528(B)	20TQC8R2M	Sanyo
1	C3	4.7 μ F	Capacitor, Ceramic, Low Inductance, 6.3 V, X5R, 20%	0603	GRM188R60J475ME19D	muRata
0	C4	Open	Capacitor, Ceramic, Low Inductance, 6.3 V, X5R, 20%	0603	GRM188R60J106ME47D	muRata
1	C5	15 pF	Capacitor, Ceramic, 50 V, C0G-NP0, 5%	0603	Std	Std
1	L1	18 μ H	Inductor, SMT, 0.56 A, 750milliohm	0.118 x 0.118 inch	LPS3015-183ML	Coilcraft
1	R1	301k	Resistor, Chip, 1/16W, 1%	0603	Std	Std
1	R2	243k	Resistor, Chip, 1/16W, 1%	0603	Std	Std
1	U1	TPS62122DRV	IC, 15V, 75mA High-Efficiency Buck Converter with Snooze Mode	SON-6 [DRV]	TPS62122DRV	TI

Evaluation Board/Kit Important Notice

Texas Instruments (TI) provides the enclosed product(s) under the following conditions:

This evaluation board/kit is intended for use for **ENGINEERING DEVELOPMENT, DEMONSTRATION, OR EVALUATION PURPOSES ONLY** and is not considered by TI to be a finished end-product fit for general consumer use. Persons handling the product(s) must have electronics training and observe good engineering practice standards. As such, the goods being provided are not intended to be complete in terms of required design-, marketing-, and/or manufacturing-related protective considerations, including product safety and environmental measures typically found in end products that incorporate such semiconductor components or circuit boards. This evaluation board/kit does not fall within the scope of the European Union directives regarding electromagnetic compatibility, restricted substances (RoHS), recycling (WEEE), FCC, CE or UL, and therefore may not meet the technical requirements of these directives or other related directives.

Should this evaluation board/kit not meet the specifications indicated in the User's Guide, the board/kit may be returned within 30 days from the date of delivery for a full refund. **THE FOREGOING WARRANTY IS THE EXCLUSIVE WARRANTY MADE BY SELLER TO BUYER AND IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED, IMPLIED, OR STATUTORY, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE.**

The user assumes all responsibility and liability for proper and safe handling of the goods. Further, the user indemnifies TI from all claims arising from the handling or use of the goods. Due to the open construction of the product, it is the user's responsibility to take any and all appropriate precautions with regard to electrostatic discharge.

EXCEPT TO THE EXTENT OF THE INDEMNITY SET FORTH ABOVE, NEITHER PARTY SHALL BE LIABLE TO THE OTHER FOR ANY INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES.

TI currently deals with a variety of customers for products, and therefore our arrangement with the user **is not exclusive**.

TI assumes **no liability for applications assistance, customer product design, software performance, or infringement of patents or services described herein**.

Please read the User's Guide and, specifically, the Warnings and Restrictions notice in the User's Guide prior to handling the product. This notice contains important safety information about temperatures and voltages. For additional information on TI's environmental and/or safety programs, please contact the TI application engineer or visit www.ti.com/esh.

No license is granted under any patent right or other intellectual property right of TI covering or relating to any machine, process, or combination in which such TI products or services might be or are used.

FCC Warning

This evaluation board/kit is intended for use for **ENGINEERING DEVELOPMENT, DEMONSTRATION, OR EVALUATION PURPOSES ONLY** and is not considered by TI to be a finished end-product fit for general consumer use. It generates, uses, and can radiate radio frequency energy and has not been tested for compliance with the limits of computing devices pursuant to part 15 of FCC rules, which are designed to provide reasonable protection against radio frequency interference. Operation of this equipment in other environments may cause interference with radio communications, in which case the user at his own expense will be required to take whatever measures may be required to correct this interference.

EVM Warnings and Restrictions

It is important to operate this EVM within the input voltage range of 2 V to 15 V and the output voltage range of 1.2 V to 5.5 V.

Exceeding the specified input range may cause unexpected operation and/or irreversible damage to the EVM. If there are questions concerning the input range, please contact a TI field representative prior to connecting the input power.

Applying loads outside of the specified output range may result in unintended operation and/or possible permanent damage to the EVM. Please consult the EVM User's Guide prior to connecting any load to the EVM output. If there is uncertainty as to the load specification, please contact a TI field representative.

During normal operation, some circuit components may have case temperatures greater than +60°C. The EVM is designed to operate properly with certain components above +60°C as long as the input and output ranges are maintained. These components include but are not limited to linear regulators, switching transistors, pass transistors, and current sense resistors. These types of devices can be identified using the EVM schematic located in the EVM User's Guide. When placing measurement probes near these devices during operation, please be aware that these devices may be very warm to the touch.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products		Applications	
Amplifiers	amplifier.ti.com	Audio	www.ti.com/audio
Data Converters	dataconverter.ti.com	Automotive	www.ti.com/automotive
DLP® Products	www.dlp.com	Communications and Telecom	www.ti.com/communications
DSP	dsp.ti.com	Computers and Peripherals	www.ti.com/computers
Clocks and Timers	www.ti.com/clocks	Consumer Electronics	www.ti.com/consumer-apps
Interface	interface.ti.com	Energy	www.ti.com/energy
Logic	logic.ti.com	Industrial	www.ti.com/industrial
Power Mgmt	power.ti.com	Medical	www.ti.com/medical
Microcontrollers	microcontroller.ti.com	Security	www.ti.com/security
RFID	www.ti-rfid.com	Space, Avionics & Defense	www.ti.com/space-avionics-defense
RF/IF and ZigBee® Solutions	www.ti.com/lprf	Video and Imaging	www.ti.com/video
		Wireless	www.ti.com/wireless-apps