



Recommended PCB Layout
(Top View)



Material and Finish

Insulator: PBT Thermoplastic
with Glass-fiber Reinforcement,
UL 94V-0 Rated,
Color: Black

Shell: Steel, Nickel Plated

Contact Material:
Plug - Phosphor Bronze

Contact Plating Options:

Standard: Gold Flash on
Mating End, Tin on
Termination End, Nickel
Underplate on Entire Contact

15 Option: 15u" Gold on
Mating End, Tin on
Termination End, Nickel
Underplate on Entire Contact

30 Option: 30u" Gold on
Mating End, Tin on
Termination End, Nickel
Underplate on Entire Contact

Electrical Specifications

Rated Current: 2A

Rated Voltage: 30V RMS

Insulation Resistance:
1000 Megohms Min. at 500V DC

Contact Resistance:
13 milliohms Max.

Dielectric Withstanding Voltage:
1000V for 1 Minute

Mechanical Specifications

Operating Temperature:
-55°C to +105°C

Part Number	Contact Area Plating Finish
K31X-E9P-NJ	Gold Flash (Standard)
K31X-E9P-NJ15	15u" Gold (15 Option)
K31X-E9P-NJ30	30u" Gold (30 Option)

RoHS COMPLIANT



Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	03/24/06	New Drawing	R. Aguirre	H. MA	R. Aguirre	03/23/06
A2	3/6/08	ECO #07-051	S. Vien	H. MA		
A3	10/01/12	ECO #12-052	S. Vien	P. DalCanto		
A4	12/31/17	ECO #17-041	G. Serrato	C. Furumasa		

K31X-E9P-NJ

D-Sub, 9Pin, Plug, Ultra Compact Footprint

Jackscrews Installed, RoHS Compliant

