

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0795405067

Status:

Active

Overview:

In-Vehicle Smart Charging Modules

Description:

In-Vehicle Dual Port Smart Charger, USB Type A and C, with Backlight, 3.0A USB-C / 2.4A USB-A



Documents:

[Drawing \(PDF\)](#)

[RoHS Certificate of Compliance \(PDF\)](#)

[Datasheet \(PDF\)](#)

| General                        |                                   |
|--------------------------------|-----------------------------------|
| Product Family                 | I/O Connectors                    |
| Series                         | 79540                             |
| Application                    | Module-to-Wire                    |
| Component Type                 | USB Charger                       |
| Overview                       | In-Vehicle Smart Charging Modules |
| Product Name                   | Mini50, USB                       |
| Type                           | A, C                              |
| UPC                            | 191128872768                      |
| Physical                       |                                   |
| Circuits (Loaded)              | 2                                 |
| Circuits (maximum)             | 4                                 |
| Color - Resin                  | Black                             |
| Durability (mating cycles max) | 10000                             |
| Lock to Mating Part            | Yes                               |
| Material - Plating Mating      | N/A                               |
| Material - Resin               | ABS, PC                           |
| Net Weight                     | 43.431/g                          |
| Number of Rows                 | 1                                 |
| Orientation                    | Vertical                          |
| Packaging Type                 | Bag                               |
| Panel Mount                    | Yes                               |
| Pitch - Mating Interface       | N/A                               |
| Polarized to Mating Part       | Yes                               |
| Ports                          | 2                                 |
| Temperature Range - Operating  | -40° to +85°C                     |
| Termination Interface: Style   | N/A                               |
| Waterproof / Dustproof         | No                                |
| Electrical                     |                                   |
| Current - Maximum per Contact  | 2.4A, 3.0A                        |
| Material Info                  |                                   |
| Reference - Drawing Numbers    |                                   |
| Sales Drawing                  | 795405067-000                     |

|                                                               |                                                 |
|---------------------------------------------------------------|-------------------------------------------------|
| EU ELV                                                        |                                                 |
| Not Relevant                                                  |                                                 |
| EU RoHS                                                       | China RoHS                                      |
| Compliant with Exemption 7(a),7(c)-I*                         |                                                 |
| REACH SVHC                                                    |                                                 |
| Not Reviewed                                                  |                                                 |
| Halogen-Free                                                  |                                                 |
| Status                                                        |                                                 |
| Not Reviewed                                                  |                                                 |
| For more information, please visit <a href="#">Contact US</a> |                                                 |
| CUST_NOTE                                                     | *Product contains part(s) with customer managed |
| CUST_NOTE1                                                    | EHS data. These part(s) are excluded from       |
| CUST_NOTE2                                                    | product compliance status evaluation.           |
| China ROHS                                                    | 50 Image                                        |
| ELV                                                           | Not Relevant                                    |
| RoHS Phthalates                                               | Not Contained*                                  |

Search Parts in this Series

79540 Series

Mates With

USB Type A and USB Type C (Front)<br>Mini50 Unsealed Receptacle 34791-0040 (Rear)

Use With

16V DC

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION