


REVISIONS				
REV	ECR	DESCRIPTION	DRAWN	DATE
1		ENGINEERING RELEASE	P. BURDGE	07/23/2020

-XX IN THE ENDING OF THE CABLE PART NUMBER IS CALLING OUT THE LENGTH OF THE ASSEMBLY FROM CENTER TO CENTER OF CONNECTORS. EXAMPLES SHOWN BELOW:

LTI P/N: CB1.37-2IPX-7IN (7 INCHES)
CB1.37-2IPX-10.5IN (10.5 INCHES)



LENGTH TOLERANCE FOR CABLE ASSEMBLIES	
Inches	Millimeters
0 - 2IN +/- 0.040	0 - 51 +/- 1
2IN - 6IN +/- 0.080	51 - 153 +/- 2
6IN - 12IN +/- 0.140	153 - 305 +/- 3.5
12IN - 48IN +/- 0.250	305 - 1219 +/- 6.4
48IN - 144IN (12FT) +/- 0.500	1219 - 3658 +/- 13
144IN (12FT) - ABOVE +/- 1.0	3658 - ABOVE +/- 25
UNLESS OTHERWISE SPECIFIED ON DRAWING	

ITEM	PART NUMBER	DESCRIPTION	QTY
1	1.37 MICRO COAX	CABLE, 1.37 MICRO COAX, BLUE	AR
2	IPXLF11GPB-137	IPX(MHF1), RHT ANGLE, JACK, CABLE CRIMP	2

MHF IS A REGISTAERED TRADEMARK OF I-PEX CO., LTD. CORPORATION

DO NOT SCALE DRAWING TOLERANCES UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS X = ±0.5 X.X = ±0.25 X.XX = ±0.13 ANGLE = ±30'			 Lighthorse Technologies San Diego, CA WWW.RFCONNECTOR.COM		
 THIRD ANGLE PROJECTION			TITLE: CABLE ASSEMBLY, IPX (MHF1), R/A JACK, CRIMP TO IPX (MHF1), R/A JACK, CRIMP USING 1.37 MICRO COAX, BLUE		
CUSTOMER APPROVAL			SIZE	PART/DWG. NO:	REV
SIGN / DATE:			B	CB1.37-2IPX-XX	1
ENG APPR.					
CHECKED					
DRAWN	P. BURDGE	07/23/2020			
	NAME	DATE	SCALE: 4:1	FILE NAME	SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL

UNLESS OTHERWISE SPECIFIED: THIS DOCUMENT CONTAINS LIGHTHORSE TECHNOLOGIES INFORMATION, REPRODUCTION, USE, DISCLOSURE OR TRANSMITTAL OF ALL OR ANY PART OF THIS DOCUMENT IS PROHIBITED EXCEPT TO THE EXTENT APPROVED IN WRITING BY AN AUTHORIZED REPRESENTATIVE OF LIGHTHORSE TECHNOLOGIES. LIGHTHORSE TECHNOLOGIES RESERVES ALL RIGHTS UNDER PATENTS, TRADEMARKS, COPY RIGHTS AND TRADE SECRETS. COPY RIGHTS OF LIGHTHORSE TECHNOLOGIES 2011, ALL RIGHTS RESERVED.

