



Automotive P-Channel 12 V (D-S) 175 °C MOSFET



FEATURES

- TrenchFET® power MOSFET
- AEC-Q101 qualified
- 100 % R_g and UIS tested
- Material categorization:
for definitions of compliance please see www.vishay.com/doc?99912



PRODUCT SUMMARY	
V_{DS} (V)	-12
$R_{DS(on)}$ (Ω) at $V_{GS} = -4.5$ V	0.0040
$R_{DS(on)}$ (Ω) at $V_{GS} = -2.5$ V	0.0064
I_D (A)	-238
Configuration	Single

ORDERING INFORMATION	
Package	PowerPAK SO-8L
Lead (Pb)-free and halogen-free	SQJ123ELP (for detailed order number please see www.vishay.com/doc?79776)

ABSOLUTE MAXIMUM RATINGS ($T_C = 25$ °C, unless otherwise noted)			
PARAMETER	SYMBOL	LIMIT	UNIT
Drain-source voltage	V_{DS}	-12	V
Gate-source voltage ^a	V_{GS}	± 8	
Continuous drain current	I_D	-238	
		-137	
Continuous source current (diode conduction) ^b	I_S	-340	A
Pulsed drain current ^c	I_{DM}	400	
Single pulse avalanche current	I_{AS}	73	
Single pulse avalanche energy	E_{AS}	270	
Maximum power dissipation ^c	P_D	375	W
		125	
Operating junction and storage temperature range	T_J, T_{stg}	-55 to +175	°C
Soldering recommendations (peak temperature) ^{d, e}		260	

THERMAL RESISTANCE RATINGS			
PARAMETER	SYMBOL	LIMIT	UNIT
Junction-to-ambient	R_{thJA}	44	°C/W
Junction-to-case (drain)	R_{thJC}	0.4	

Notes







- Not intended for continuous use with positive gate voltage > 5.0 V
- Package limited
- When mounted on 1" square PCB (FR4 material)
- See solder profile (www.vishay.com/doc?273257). For PowerPAK SO-8L, the end of the lead terminal is exposed copper (not plated) as a result of the singulation process in manufacturing. A solder fillet at the exposed copper tip cannot be guaranteed and is not required to ensure adequate bottom side solder interconnection
- Rework conditions: manual soldering with a soldering iron is not recommended for leadless components
- Pulse test; pulse width ≤ 300 μ s, duty cycle ≤ 2 %







SPECIFICATIONS ($T_C = 25^\circ\text{C}$, unless otherwise noted)								
PARAMETER	SYMBOL	TEST CONDITIONS		MIN.	TYP.	MAX.	UNIT	
Static								
Drain-source breakdown voltage	V_{DS}	$V_{GS} = 0$, $I_D = -250 \mu\text{A}$		-12	-	-	V	
Gate-source threshold voltage	$V_{GS(\text{th})}$	$V_{DS} = V_{GS}$, $I_D = -250 \mu\text{A}$		-0.45	-0.6	-1.5		
Gate-source leakage	I_{GSS}	$V_{DS} = 0 \text{ V}$, $V_{GS} = \pm 8 \text{ V}$		-	-	± 100	nA	
Zero gate voltage drain current	I_{DSS}	$V_{GS} = 0 \text{ V}$	$V_{DS} = -12 \text{ V}$	-	-	-1	μA	
		$V_{GS} = 0 \text{ V}$	$V_{DS} = -12 \text{ V}$, $T_J = 125^\circ\text{C}$	-	-	-50		
		$V_{GS} = 0 \text{ V}$	$V_{DS} = -12 \text{ V}$, $T_J = 175^\circ\text{C}$	-	-	-150		
On-state drain current ^a	$I_{D(\text{on})}$	$V_{GS} = -4.5 \text{ V}$	$V_{DS} \geq -5 \text{ V}$	-30	-	-	A	
Drain-source on-state resistance ^a	$R_{DS(\text{on})}$	$V_{GS} = -4.5 \text{ V}$	$I_D = -10 \text{ A}$	-	0.0029	0.0040	Ω	
		$V_{GS} = -4.5 \text{ V}$	$I_D = -10 \text{ A}$, $T_J = 125^\circ\text{C}$	-	-	0.0057		
		$V_{GS} = -4.5 \text{ V}$	$I_D = -10 \text{ A}$, $T_J = 175^\circ\text{C}$	-	-	0.0066		
		$V_{GS} = -2.5 \text{ V}$	$I_D = -10 \text{ A}$	-	0.0040	0.0064		
		$V_{GS} = -1.8 \text{ V}$	$I_D = -8 \text{ A}$	-	0.0070	0.0012		
Forward transconductance ^b	g_{fs}	$V_{DS} = -6 \text{ V}$, $I_D = -20 \text{ A}$		-	82	-	S	
Dynamic ^b								
Input capacitance	C_{iss}	$V_{GS} = 0 \text{ V}$	$V_{DS} = -6 \text{ V}$, $f = 1 \text{ MHz}$	-	8342	11 680	pF	
Output capacitance	C_{oss}			-	3173	4443		
Reverse transfer capacitance	C_{rss}			-	2844	3982		
Total gate charge ^c	Q_g	$V_{GS} = -4.5 \text{ V}$	$V_{DS} = -6 \text{ V}$, $I_D = -15 \text{ A}$	-	120	180	nC	
Gate-source charge ^c	Q_{gs}			-	15	-		
Gate-drain charge ^c	Q_{gd}			-	38	-		
Gate resistance	R_g	$f = 1 \text{ MHz}$		1.1	2.2	3.3	Ω	
Turn-on delay time ^c	$t_{d(\text{on})}$	$V_{DD} = -6 \text{ V}$, $R_L = 0.4 \Omega$, $I_D \equiv -15 \text{ A}$, $V_{GEN} = -4.5 \text{ V}$, $R_g = 1 \Omega$		-	31	47	ns	
Rise time ^c	t_r			-	53	80		
Turn-off delay time ^c	$t_{d(\text{off})}$			-	181	272		
Fall time ^c	t_f			-	126	189		
Source-Drain Diode Ratings and Characteristics ^b								
Pulsed current ^a	I_{SM}			-	-	-1360	A	
Forward voltage	V_{SD}	$I_F = -10 \text{ A}$, $V_{GS} = 0 \text{ V}$		-	-0.76	-1.2	V	
Body diode reverse recovery time	t_{rr}	$I_F = -10 \text{ A}$, $\text{di/dt} = 100 \text{ A}/\mu\text{s}$, $V_{DD} = 9 \text{ V}$, $R_L = 10 \Omega$, $L = 0.1 \text{ mH}$		-	105	210	ns	
Body diode reverse recovery charge	Q_{rr}			-	172	346		
Reverse recovery fall time	t_a			-	51	-		
Reverse recovery rise time	t_b			-	56	-		
Body diode peak reverse recovery current	$I_{RM(\text{REC})}$			-	-2.8	-	A	

Notes



- a. Pulse test; pulse width $\leq 300 \mu\text{s}$, duty cycle $\leq 2 \%$
- b. Guaranteed by design, not subject to production testing
- c. Independent of operating temperature

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, unless otherwise noted)

Output Characteristics

Transfer Characteristics

Transconductance

On-Resistance vs. Drain Current

Capacitance

Gate Charge

TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$, unless otherwise noted)

On-Resistance vs. Junction Temperature

Source Drain Diode Forward Voltage

On-Resistance vs. Gate-to-Source Voltage

Threshold Voltage

Drain-Source Breakdown vs. Junction Temperature

Safe Operating Area
Note

a. $V_{GS} >$ minimum V_{GS} at which $R_{DS(on)}$ is specified


THERMAL RATINGS ($T_C = 25^\circ\text{C}$, unless otherwise noted)

Normalized Thermal Transient Impedance, Junction-to-Ambient

Normalized Thermal Transient Impedance, Junction-to-Case
Note

- The characteristics shown in the two graphs
 - Normalized Transient Thermal Impedance Junction-to-Ambient (25°C)
 - Normalized Transient Thermal Impedance Junction-to-Case (25°C)

are given for general guidelines only to enable the user to get a "ball park" indication of part capabilities. The data are extracted from single pulse transient thermal impedance characteristics which are developed from empirical measurements. The latter is valid for the part mounted on printed circuit board - FR4, size 1" x 1" x 0.062", double sided with 2 oz. copper, 100 % on both sides. The part capabilities can widely vary depending on actual application parameters and operating conditions

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package / tape drawings, part marking, and reliability data, see www.vishay.com/ppg?79217.

PowerPAK® SO-8L Case Outline 3



DIM.	MILLIMETERS			INCHES		
	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
A	1.00	1.05	1.10	0.039	0.041	0.043
A1	0.00	---	0.127	0.000	---	0.005
A2	0.40	0.45	0.50	0.016	0.018	0.020
b	0.33	0.41	0.49	0.013	0.016	0.019
b1	0.43	0.51	0.59	0.017	0.020	0.023
b2	4.00	4.10	4.20	0.157	0.161	0.165
c	0.15	0.20	0.25	0.006	0.008	0.010
D1	4.80	4.90	5.00	0.189	0.193	0.197
D2	3.86	3.96	4.06	0.152	0.156	0.160
D5	0.51	0.61	0.71	0.020	0.024	0.028
D6	2.64	2.74	2.84	0.104	0.108	0.112
e	1.27 BSC			0.050 BSC		
E	6.05	6.15	6.25	0.238	0.242	0.246
E1	4.27	4.37	4.47	0.168	0.172	0.176
E2	3.18	3.28	3.38	0.125	0.129	0.133
E3	3.48	3.58	3.68	0.137	0.141	0.145
E4	2.72	2.82	2.92	0.107	0.111	0.115
E5	0.71	0.81	0.91	0.028	0.032	0.036
L	0.62	0.72	0.82	0.024	0.028	0.032
L1	0.92	1.07	1.22	0.036	0.042	0.048
W1	0.31	0.41	0.51	0.012	0.016	0.020
W4	0.31	0.36	0.41	0.012	0.014	0.016
z1	0.37	0.47	0.57	0.015	0.019	0.022
z2	0.99	1.09	1.19	0.039	0.043	0.047
θ	0°	---	5°	0°	---	5°


ECN: S19-0643-Rev. B, 05-Aug-2019

DWG: 6067

Note

- Millimeter will govern

Recommended Land Pattern PowerPAK® SO-8L Single Short Ear



Dimensions in Millimeters (Inches)

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.