

ATGBICS MCP1650-H00AE30 NVIDIA Mellanox Compatible Direct Attach Copper Twinax Cable 200G-CU HDR QSFP56 (0.5m, Passive)



Brand : ATGBICS

Product code: MCP1650-H00AE30-C

Product name : MCP1650-H00AE30 NVIDIA Mellanox Compatible Direct Attach Copper Twinax Cable 200G-CU HDR QSFP56 (0.5m, Passive)



MCP1650-H00AE30 NVIDIA Mellanox Compatible Direct Attach Copper Twinax Cable 200G-CU HDR QSFP56 (0.5m, Passive)


ATGBICS MCP1650-H00AE30 NVIDIA Mellanox Compatible Direct Attach Copper Twinax Cable 200G-CU HDR QSFP56 (0.5m, Passive):

ATGBICS MCP1650-H00AE30 compatible 200GBase-CU QSFP+ to QSFP+ direct attach cable operates over passive copper with a cable length of 0.5m. It is suitable for short reach connection between two QSFP+ ports in 200G interconnecting networking applications.

Our product meets or exceeds the specification of NVIDIA Mellanox MCP1650-H00AE30= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards and protocols including; 40G InfiniBand 4x FDR, 200Gigabit Ethernet, Fibre Channel .

ATGBICS MCP1650-H00AE30 NVIDIA Mellanox Compatible Direct Attach Copper Twinax Cable 200G-CU HDR QSFP56 (0.5m, Passive). Cable length: 0.5 m, Connector 1: QSFP+, Connector 2: QSFP+, Connector gender: Male/Male

Features		Features	
Cable length *	0.5 m	Conductor material	Copper
AWG wire size	26	Brand compatibility	Mellanox
Cable shape	Round	Plug and Play	✓
Connector 1 *	QSFP+	Country of origin	United Kingdom
Connector 2 *	QSFP+	Certification	CE, FCC, RoHS
Connector gender	Male/Male	Technical details	
Connector 1 gender *	Male	Sustainability certificates	RoHS
Connector 2 gender *	Male	Operational conditions	
Product colour *	Black	Operating temperature (T-T)	0 - 70 °C
Ethernet interface type	200 Gigabit Ethernet	Storage temperature (T-T)	-40 - 80 °C
Data transfer rate	200 Gbit/s	Packaging data	
Data transfer rate	200000 Mbit/s	Quantity per pack	1 pc(s)
Jacket material *	Optical fiber non-conductive riser (OFNR), Polyvinyl chloride (PVC)	Other features	
		Networking standards	IEEE 802.3cd



5056468760630

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.