



Passive Components > Resistors > Through-Hole Resistors > Wirewound Resistor: Vertical Mount



Resistor Type: **Power Resistor**
Element Type: **Wire Wound**
Power Rating: **17 W**
Resistance Class: **Up to 1k Ω**
Resistance Value: **1.5 Ω**

[All Wirewound Resistor: Vertical Mount \(137\)](#)

Features

Product Type Features

Resistor Type	Power Resistor
Element Type	Wire Wound

Configuration Features

Number of Resistors	1
---------------------	---

Electrical Characteristics

Power Rating	17 W
Resistance Class	Up to 1k Ω
Resistance Value	1.5 Ω
Passive Component Tolerance	10 %

Body Features

Lead Type	Axial-Leaded
-----------	--------------

Termination Features

Termination Area Base Material	Copper
Number of Terminations	2

Dimensions

Passive Component Dimensions	75 x 10 x 9 mm
------------------------------	----------------



Usage Conditions

Operating Temperature Range	-55 - 350 °C
Temperature Coefficient	±400 ppm/°C

Packaging Features

Packaging Method	Loose Piece - Box
------------------	-------------------

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

SBCHE151R5K

Power Resistor, Wire Wound, 17 W, 1.5 Ω , 10 %, ± 400 ppm/ $^{\circ}\text{C}$, Axial-Leaded, Copper Termination, 75 x 10 x 9 mm, Loose Piece - Box, CGS SBC



TE Part # 1623729-1
BCHE 17 W 100R 5%

TE Part # 1623728-3
BCHE 11 W 10R 5%

TE Part # 1-1623728-1
BCHE 11 W 220R 5%

TE Part # 1-1623728-2
BCHE 11 W 22K 5%

TE Part # 2-1623728-2
BCHE 11 W 47R 5%

Also in the Series | CGS SBC

Surface Mount Resistors(1)

Through-Hole Resistors(212)

Customers Also Bought

TE Part # 1-1623729-3
BCHE 17 W 22R 5%

TE Part # 2-1625971-0
HSA25 1R2 5%

TE Part # 1393845-5
RP821024

TE Part # 1614881-1
CPF0603 10K 0.1% 25PPM 5K RL

TE Part # 1623767-2
23E 1MA 6.35X50FL B7 CAT

TE Part # 1676480-3
CRG0402 1% 10K

TE Part # 4-1879494-9
CRGH0603 5% 100R 0.2W

TE Part # 9-1462038-9
IM03DGR=IM RELAY 140mW 5V



Documents

Product Drawings

BCHE 17 W 1R5 10%

English

Datasheets & Catalog Pages

4-1773460-6_RESISTIVE_SOLUTIONS_RAIL

English

1309350_PASSIVE_COMPONENT

English

8-1773459-4_POWER_FILTERING_AND_RESISTIVE_SOLUTIONS_FOR_ELEVATORS_AND_ESCALATORS

English

High Power Resistor - Type SBC (Square Ceramic) Series - Tyco Electronics Passives

English