

WIREFOX 16 - Stripping tool

1212155

<https://www.phoenixcontact.com/us/products/1212155>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Stripping tool, for cables and conductors from 4 - 16 mm², self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm² stranded/1.5 mm² solid, replaceable stripping blade

Product description

Insertable stripping blades: 1212151 WIREFOX 4/SB, 1212152 WIREFOX 10/SB, and 1212314 WIREFOX 6SC/SB, direct replacement: 1212153 WIREFOX 16/SB

Your advantages

- Flexible, adjustable limit stop for the stripping length
- Practical integrated wire cutter
- WIREFOX ... stripping pliers feature an automatic adjustment mechanism for a wide range of different types of insulation and conductor diameters

Commercial data

Item number	1212155
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BH31
Product key	BH3121
Catalog page	Page 407 (C-3-2019)
GTIN	4046356454414
Weight per piece (including packing)	210.3 g
Weight per piece (excluding packing)	210 g
Customs tariff number	82032000
Country of origin	SE

WIREFOX 16 - Stripping tool

1212155

<https://www.phoenixcontact.com/us/products/1212155>



Technical data

Notes

Environmental Product Compliance

California Proposition 65

Further information on California's prop. 65 is available under "Downloads" in the manufacturer's declaration

Product properties

Product type	Stripping tool
Application	Standard

Connection data

Conductor connection

Cross section range, metric	4 mm ² ... 16 mm ² (Stripping range) 1.5 mm ² (Cutting zone)
Cross section range AWG	12 ... 5 (Stripping range) 16 (Cutting zone)
Stripping length	2 mm ... 18 mm

Dimensions

Width	20 mm
Height	90 mm
Length	191 mm

Material specifications

Color	black/green
-------	-------------

WIREFOX 16 - Stripping tool

1212155

<https://www.phoenixcontact.com/us/products/1212155>



Approvals

ⓘ To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1212155>



EAC

Approval ID: RU x-DE.xx08.B.02974

WIREFOX 16 - Stripping tool

1212155

<https://www.phoenixcontact.com/us/products/1212155>



Classifications

ECLASS

ECLASS-11.0	21043706
ECLASS-12.0	21043706
ECLASS-13.0	21043706

ETIM

ETIM 9.0	EC002109
----------	----------

UNSPSC

UNSPSC 21.0	27111500
-------------	----------

WIREFOX 16 - Stripping tool

1212155

<https://www.phoenixcontact.com/us/products/1212155>



Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements

Not applicable, No electrical and electronic equipment (EEE), cannot be used in EEE

EU REACH SVHC

REACH candidate substance (CAS No.)

No substance above 0.1 wt%

WIREFOX 16 - Stripping tool



1212155

<https://www.phoenixcontact.com/us/products/1212155>

Accessories

WIREFOX 16/SB - Spare knife

1212153

<https://www.phoenixcontact.com/us/products/1212153>

Replacement blade for WIREFOX 16, for cables and conductors of 4 - 16 mm²



WIREFOX 10/WS - Replacement limit stop

1200285

<https://www.phoenixcontact.com/us/products/1200285>

Replacement limit stop



WIREFOX 16 - Stripping tool

1212155

<https://www.phoenixcontact.com/us/products/1212155>



WIREFOX 16/CJ - Replacement retaining jaw

1200287

<https://www.phoenixcontact.com/us/products/1200287>

Replacement clamping jaws for WIREFOX 16



WIREFOX 4/SB - Spare knife

1212151

<https://www.phoenixcontact.com/us/products/1212151>

Replacement blade for WIREFOX 4, for cables and conductors (especially for rubber and silicone insulations) of 0.1 - 4 mm²



WIREFOX 16 - Stripping tool

1212155

<https://www.phoenixcontact.com/us/products/1212155>



WIREFOX 10/SB - Spare knife

1212152

<https://www.phoenixcontact.com/us/products/1212152>



Replacement blade for WIREFOX 10, for cables and conductors of 0.02 - 10 mm²

WIREFOX 6SC/SB - Spare knife

1212314

<https://www.phoenixcontact.com/us/products/1212314>



Replacement blade for WIREFOX 6SC, for cables and conductors (especially for cables protected against short circuits and ground leakages) 1.5 - 6 mm²

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com