

DT-UFB-IB-RB0 - Surge protection device



2800056
<https://www.phoenixcontact.com/us/products/2800056>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Attachment plug with surge protection for 5-conductor remote bus input. Connection: 9-pos. D-SUB socket - plug. Can alternatively be snapped onto DIN rails. Incl. 1 m cable with 9-pos. D-SUB connection.

Your advantages

- Easy network integration via D-SUB connection
- No signal interference with adapted protective circuit
- Can be installed in a control cabinet by removing the ground connection adapter

Commercial data

Item number	2800056
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	CL24
Product key	CL3112
Catalog page	Page 183 (C-4-2019)
GTIN	4046356462723
Weight per piece (including packing)	440.1 g
Weight per piece (excluding packing)	436 g
Customs tariff number	85363010
Country of origin	DE

DT-UFB-IB-RB0 - Surge protection device



2800056
<https://www.phoenixcontact.com/us/products/2800056>

Technical data

Product properties

Product type	Surge protection for information technology
Product family	DATATRAB
IEC test classification	B2
	C1
	C2
	C3
	D1
VDE requirement class	B2
	C1
	C2
	C3
	D1
Type	Attachment plug for DIN rail mounting
Number of positions	5
Wire pairs per module	2

Insulation characteristics

Overvoltage category	II
----------------------	----

Connection data

Connection method	D-SUB-9
-------------------	---------

Dimensions

Dimensional drawing	
Width	25 mm
Height	110 mm
Depth	63 mm

Material specifications

Color	Silver
	black (RAL 9005)
Housing material	Zinc die-cast

Mechanical properties

Mechanical data

DT-UFB-IB-RB0 - Surge protection device



2800056

<https://www.phoenixcontact.com/us/products/2800056>

Open side panel	No
-----------------	----

Protective circuit

Direction of action	Line-Line & Line-Ground/Shield
Maximum continuous voltage U_C	5.8 V DC
Rated current	≤ 180 mA (25 °C)
Operating effective current I_C at U_C	≤ 1 μ A
Residual current I_{PE}	≤ 5 μ A
Nominal discharge current I_n (8/20) μ s (line-line)	≤ 5 kA
Nominal discharge current I_n (8/20) μ s (line-ground)	≤ 5 kA
Total discharge current I_{total} (8/20) μ s	10 kA
Output voltage limitation at 1 kV/ μ s (line-earth) spike	≤ 700 V
Output voltage limitation at 1 kV/ μ s (line-line) static	≤ 15 V
Output voltage limitation at 1 kV/ μ s (line-earth) static	≤ 700 V
Output voltage limitation at 1 kV/ μ s (line-signalground) static	≤ 15 V
Residual voltage at I_n (conductor-conductor)	≤ 25 V
Residual voltage at I_n (conductor-ground)	≤ 55 V
Residual voltage at I_n (line-signalground)	≤ 25 V
Voltage protection level U_p (line-line)	≤ 16 V (B2 - 100 A)
	≤ 20 V (C1 - 500 A)
	≤ 60 V (C2 - 1 kA)
	≤ 60 V (C2 - 5 kA)
Voltage protection level U_p (line-earth)	≤ 700 V (B2 - 100 A)
	≤ 700 V (C1 - 500 A)
	≤ 700 V (C2 - 5 kA)
Response time t_A (line-line)	≤ 1 ns
Response time t_A (line-earth)	≤ 100 ns
Input attenuation aE, sym.	typ. 0.5 dB (≤ 5 MHz / 150 Ω)
	typ. 0.6 dB (≤ 10 MHz / 100/150 Ω)
Cut-off frequency f_g (3 dB), sym. in 100 Ω system	≥ 100 MHz
Cut-off frequency f_g (3 dB), sym. in 150 Ω system	≥ 100 MHz
Capacity (Core-Core)	typ. 20 pF
Resistance per path	typ. 7 Ω
Surge protection fault message	none
Impulse durability (line-line)	C1 - 1 kV / 500 A
	C2 - 10 kV / 5 kA
	B2 - 4 kV / 100 A
Impulse durability (line-earth)	B2 - 4 kV / 100 A
	C1 - 1 kV / 500 A
	C2 - 10 kV / 5 kA
	D1 - 1 kA

Environmental and real-life conditions

Ambient conditions

DT-UFB-IB-RB0 - Surge protection device



2800056

<https://www.phoenixcontact.com/us/products/2800056>

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 85 °C

Standards and regulations

VDE requirement class	B2
	C1
	C2
	C3
	D1

Air clearances and creepage distances

Standards/regulations	IEC 60664-1 / VDE 0110-1
-----------------------	--------------------------

Standards Information technology specification

Standards/regulations	IEC 61643-21
	DIN EN 61643-21
	IEC 61643-21
	DIN EN 61643-21
Standards/specifications	DIN EN 61643-21
Note	2002
Standards/specifications	IEC 61643-21
Note	2000

Mounting

Mounting type	Connection-specific attachment plug and DIN rail, 35 mm
---------------	---

DT-UFB-IB-RB0 - Surge protection device


2800056

<https://www.phoenixcontact.com/us/products/2800056>




Drawings

Circuit diagram



Dimensional drawing



DT-UFB-IB-RB0 - Surge protection device



2800056

<https://www.phoenixcontact.com/us/products/2800056>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2800056>



EAC

Approval ID: RU C-DE.*09.B.00169

DT-UFB-IB-RB0 - Surge protection device



2800056

<https://www.phoenixcontact.com/us/products/2800056>

Classifications

ECLASS

ECLASS-11.0	27130807
ECLASS-13.0	27171503

ETIM

ETIM 9.0	EC001466
----------	----------

UNSPSC

UNSPSC 21.0	39121600
-------------	----------

DT-UFB-IB-RB0 - Surge protection device



2800056
<https://www.phoenixcontact.com/us/products/2800056>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	6(a)-I, 6(c), 7(a), 7(c)-I
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	e20d13e8-0025-4ffe-a364-bbff4acfee36

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com