

# FP 1,27/ 68-FWL - IDC female connectors

1714910

<https://www.phoenixcontact.com/us/products/1714910>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



IDC female connector, nominal current: 1.2 A, Test voltage: 500 V AC, number of positions: 68, pitch: 1.27 mm, number of rows: 2, color: black, contact surface: Gold, contact connection type: Socket, For preassembled samples, see the "Accessories" tab.

## Your advantages

- Gold-plated contacts ensure transfer quality remains stable over the long term
- Compact, high-position board-to-board or wire-to-board connectors for space-saving device designs
- Can be ordered pre-assembled: IDC female connectors with flat-ribbon cable enable immediate use in the device

## Commercial data

Item number	1714910
Packing unit	120 pc
Minimum order quantity	120 pc
Sales key	AA24
Product key	AAXMAA
GTIN	4055626402895
Weight per piece (including packing)	6.47 g
Weight per piece (excluding packing)	6.14 g
Customs tariff number	85366990
Country of origin	CZ

# FP 1,27/ 68-FWL - IDC female connectors

1714910

<https://www.phoenixcontact.com/us/products/1714910>



## Technical data

### Notes

Note on application	Please observe the application note on self-assembly in the download area.
Note regarding documentation	Current documents such as 3D models, products family drawings, data sheets or packaging drawings are available in the Download Center.
Notes on operation	The permissible voltage during operation depends on the application, taking into consideration the air clearances and creepage distances within the scope of insulation requirements in accordance with IEC 60664-1.

### Product properties

Product type	IDC female connector
Product family	FR 1,27/...-FWL
Number of positions	68
Pitch	1.27 mm
Number of rows	2
Number of potentials	68

### Electrical properties

Nominal current $I_N$	1.2 A IEC 60512-5-2:2002-02 (at 20°C 50-pos.)
Contact resistance	10 mΩ
Test voltage	500 V AC IEC 60512-4-1:2003
Rated voltage (III/3)	500 V
Rated voltage (II/2)	10 V
Rated surge voltage (II/2)	0.8 kV

### Connection data

Conductor connection	
Connection method	Displacement connection
Conductor cross section AWG	30

Interlock	
Locking type	Snap-in locking
Mounting flange	Self-locking flange

### Dimensions

Pitch	1.27 mm
Width [w]	49.34 mm
Height [h]	4.2 mm
Length [l]	13.65 mm

Application	
Center offset	± 0.7 mm in longitudinal and transverse direction

# FP 1,27/ 68-FWL - IDC female connectors

1714910

<https://www.phoenixcontact.com/us/products/1714910>



Angular tolerance	± 4 ° in longitudinal direction
	± 2 ° in transverse direction

## Material specifications

### Material data - contact

Note	WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact material	Cu alloy
Surface characteristics	Selective coating
Metal surface contact area (top layer)	Gold (Au)
Metal surface contact area (middle layer)	Nickel (Ni) Palladium nickel, (PdNi)

### Material data - housing

Color (Housing)	black (9005)
Insulating material	LCP
Insulating material group	IIIb
CTI according to IEC 60112	175
Flammability rating according to UL 94	V0

## Connector

### Connection 1

Insulating material	LCP
CTI according to IEC 60112	175

## Electrical tests

### Thermal test | Test group C

Specification	IEC 60512-5-2:2002-02
Tested number of positions	50

### Insulation resistance

Specification	IEC 60512-3-1:2002-02
Insulation resistance, neighboring positions	≥ 10 GΩ

### Air clearances and creepage distances |

Insulating material group	IIIb
Rated insulation voltage (III/3)	500 V
Rated insulation voltage (II/2)	10 V
Rated surge voltage (II/2)	0.8 kV

## Mechanical tests

### Insertion and withdrawal forces

Result	Test passed
No. of cycles	500
Insertion strength per pos. approx.	0.5 N

# FP 1,27/ 68-FWL - IDC female connectors

1714910

<https://www.phoenixcontact.com/us/products/1714910>



Withdraw strength per pos. approx.	0.5 N
------------------------------------	-------

## Environmental and real-life conditions

### Vibration test

Specification	IEC 60068-2-6:2007-12
Frequency	10 - 2000 - 10 Hz
Sweep speed	1 octave/min
Amplitude	1.5 mm (10 Hz ... 60.1 Hz)
Acceleration	20g (60.1 Hz ... 2000 Hz)
Test duration per axis	2.5 h

### Durability test

Specification	IEC 60512-9-1:2010-03 (following)
Impulse withstand voltage at sea level	0.8 kV
Contact resistance $R_1$	10 mΩ
Contact resistance $R_2$	10 mΩ
Insertion/withdrawal cycles	500
Insulation resistance, neighboring positions	$\geq 10 \text{ G}\Omega$

### Climatic test

Specification	IEC 60512-11-7:2003-05
Corrosive stress	Method 1, 10 days
Power-frequency withstand voltage	500 V AC

### Shocks

Specification	IEC 60068-2-27:2008-02
Pulse shape	Semi-sinusoidal
Acceleration	50g
Shock duration	11 ms
Test directions	X-, Y- and Z-axis (pos. and neg.)

### Ambient conditions

Ambient temperature (operation)	-55 °C ... 125 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Relative humidity (storage/transport)	30 % ... 70 %
Ambient temperature (assembly)	-5 °C ... 100 °C

## Packaging specifications

Type of packaging	Tray
-------------------	------

# FP 1,27/ 68-FWL - IDC female connectors

1714910

<https://www.phoenixcontact.com/us/products/1714910>



## Classifications

### ECLASS

ECLASS-11.0	27460202
ECLASS-12.0	27460202
ECLASS-13.0	27460202

### ETIM

ETIM 9.0	EC002638
----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# FP 1,27/ 68-FWL - IDC female connectors

1714910

<https://www.phoenixcontact.com/us/products/1714910>



## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

### China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

### EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

# FP 1,27/ 68-FWL - IDC female connectors

1714910

<https://www.phoenixcontact.com/us/products/1714910>



## Accessories

### SAMPLE FP 1,27/68-FWL-11/P/0,1 - IDC female connectors

1026944

<https://www.phoenixcontact.com/us/products/1026944>



Assembled IDC female connector, rated current: 1.2 A, Cable 1: cable length: 0.1 m, Cable type: Flat cable, Flat cable

---

## FP 1,27/ 68-MV 3,25 - SMD male connectors

1714932

<https://www.phoenixcontact.com/us/products/1714932>



SMD male connector, nominal current: 1.4 A, Test voltage: 500 V AC, number of positions: 68, pitch: 1.27 mm, color: black, contact surface: Gold, contact connection type: Pin, mounting: SMD soldering

---

# FP 1,27/ 68-FWL - IDC female connectors

1714910

<https://www.phoenixcontact.com/us/products/1714910>




## FP 1,27/ 68-MV 1,75 - SMD male connectors

1714944

<https://www.phoenixcontact.com/us/products/1714944>

SMD male connector, nominal current: 1.4 A, Test voltage: 500 V AC, number of positions: 68, pitch: 1.27 mm, color: black, contact surface: Gold, contact connection type: Pin, mounting: SMD soldering



## FP 1,27/ 68-MH - SMD male connectors

1714921

<https://www.phoenixcontact.com/us/products/1714921>

SMD male connector, nominal current: 1.4 A, Test voltage: 500 V AC, number of positions: 68, pitch: 1.27 mm, color: black, contact surface: Gold, contact connection type: Pin, mounting: SMD soldering



Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA

586 Fulling Mill Road

Middletown, PA 17057, United States

(+717) 944-1300

[info@phoenixcon.com](mailto:info@phoenixcon.com)