

PSM PTK - Connection distributor

2760623

<https://www.phoenixcontact.com/us/products/2760623>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Passive RS-485 T-distributor, fitted with one 9-pin D-SUB pin strip and two 9-pin D-SUB socket strips



Commercial data

Item number	2760623
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DN10
Product key	DNC551
Catalog page	Page 443 (C-6-2019)
GTIN	4017918064327
Weight per piece (including packing)	108.933 g
Weight per piece (excluding packing)	86.1 g
Customs tariff number	85366990
Country of origin	DE

PSM PTK - Connection distributor

2760623

<https://www.phoenixcontact.com/us/products/2760623>



Technical data

Product properties

Product type	Adapter
Application	Standard
Pin assignment	all 1:1

Electrical properties

Test voltage	500 V AC (50 Hz, 1 min, rms)
Nominal voltage U_N	60 V AC/DC
Nominal current I_N	1 A
Transmission medium	Copper

Connection data

Incoming

Connection method	D-SUB 9 plug
-------------------	--------------

Outgoing

Connection method	D-SUB-9 female connector
-------------------	--------------------------

Branching

Connection method	D-SUB-9 female connector
-------------------	--------------------------

Branching

Connection method	COMBICON connectors
Conductor cross section, rigid min.	0.14 mm ²
Conductor cross section, rigid max.	1.5 mm ²
Conductor cross section flexible min.	0.14 mm ²
Conductor cross section flexible max.	1.5 mm ²
Conductor cross section AWG min.	26
Conductor cross section AWG max.	16

Interfaces

Bus system	RS-485
------------	--------

Dimensions

Width	56 mm
Height	89.6 mm
Length	48 mm

Material specifications

Color (Housing)	green (RAL 6021)
Material (Housing)	PVC
Flammability rating according to UL 94	V0

PSM PTK - Connection distributor

2760623

<https://www.phoenixcontact.com/us/products/2760623>



Cable/line

Shielding	D-SUB frame or shield clamp
-----------	-----------------------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 70 °C

Standards and regulations

Free from substances that could impair the application of coating	in accordance with VW-AUDI-Seat central standard P-VW 3.10.7 57 65 0
---	---

PSM PTK - Connection distributor


2760623

<https://www.phoenixcontact.com/us/products/2760623>



Drawings

Schematic diagram



Front view


PSM PTK - Connection distributor

2760623

<https://www.phoenixcontact.com/us/products/2760623>



Circuit diagram



PSM PTK - Connection distributor

2760623

<https://www.phoenixcontact.com/us/products/2760623>



Approvals

ⓘ To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2760623>



cUL Recognized

Approval ID: FILE E 238705



UL Recognized

Approval ID: FILE E 238705



EAC

Approval ID: RU C-DE.BL08.B.00511

cULus Recognized

PSM PTK - Connection distributor

2760623

<https://www.phoenixcontact.com/us/products/2760623>



Classifications

ECLASS

ECLASS-11.0	27141152
ECLASS-12.0	27141152
ECLASS-13.0	27141152

ETIM

ETIM 9.0	EC002780
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

PSM PTK - Connection distributor

2760623

<https://www.phoenixcontact.com/us/products/2760623>



Environmental product compliance

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

PSM PTK - Connection distributor

2760623

<https://www.phoenixcontact.com/us/products/2760623>



Accessories

SUBCON-PLUS-PROFIB/SC2 - D-SUB bus connector

2708232

<https://www.phoenixcontact.com/us/products/2708232>

D-SUB connector, 9-pos., male connector, 35° cable entry, bus system: PROFIBUS DP up to 12 Mbps, termination resistor can be switched on via slide switch, pin assignment: 3, 5, 6, 8; screw connection terminal blocks



SUBCON-PLUS-PROFIB/90/SC - D-SUB bus connector

2313698

<https://www.phoenixcontact.com/us/products/2313698>

D-SUB connector, 9-pos., male connector, 90° cable entry, bus system: PROFIBUS DP up to 12 Mbps, termination resistor can be switched on via slide switch, pin assignment: 3, 5, 6, 8; screw connection terminal blocks



PSM PTK - Connection distributor



2760623

<https://www.phoenixcontact.com/us/products/2760623>

SUBCON-PLUS-PROFIB/AX/SC - D-SUB bus connector

2744380

<https://www.phoenixcontact.com/us/products/2744380>



D-SUB connector, 9-pos., male connector, axial version with two cable entries, bus system: PROFIBUS DP up to 12 Mbps, termination resistor can be switched on via slide switch, pin assignment: 3, 5, 6, 8; screw connection terminal blocks

SUBCON-PLUS 9/F - D-SUB bus connector

2744241

<https://www.phoenixcontact.com/us/products/2744241>



D-SUB connector, 9-pos. female connector, two 35° cable entries, universal type for all systems, pin assignment: 1, 2, 3, 4, 5, 6, 7, 8, 9 to one screw connection terminal block

PSM PTK - Connection distributor

2760623

<https://www.phoenixcontact.com/us/products/2760623>



SUBCON-PLUS 9/M - D-SUB bus connector

2744018

<https://www.phoenixcontact.com/us/products/2744018>

D-SUB connector, 9-pos., male connector, two 35° cable entries, universal type for all systems, pin assignment: 1, 2, 3, 4, 5, 6, 7, 8, 9 to one screw connection terminal block



SUBCON-PLUS-M/AX 9 - D-SUB bus connector

2904467

<https://www.phoenixcontact.com/us/products/2904467>

D-SUB plug, 9-pos., pin, axial design with two cable entries, universal type for all systems, pin assignment: 1, 2, 3, 4, 5, 6, 7, 8, 9 to screw connection terminal block



PSM PTK - Connection distributor

2760623

<https://www.phoenixcontact.com/us/products/2760623>



SUBCON-PLUS-F/AX 9 - D-SUB bus connector

2311797

<https://www.phoenixcontact.com/us/products/2311797>



D-SUB connector, 9-pos. female connector, axial version with two cable entries, universal type for all systems, pin assignment: 1, 2, 3, 4, 5, 6, 7, 8, 9 to screw connection terminal block

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com